

# Cavo Technology

## FIBER OPTIC WALL MOUNTED TERMINAL BOX (SINGLE DOOR)

### FEATURES:

- Indoor Wall-mount distribution frame can manage for both single fiber and ribbon & bundle fiber special design ensures the excess fiber cords & pigtails in good order
  - They have various panel to fit different adapter interface like FC, SC, ST, LC
- Suitable for LAN / WAN, CATV application

### APPLICATION:

- Local Area Network (LAN)
- Optical Access Network (OAN)
- Data Processing Centers
- Cable Television (CATV)
- FTTH



### SPECIFICATION

ITEM		CHARACTERISTICS
Operation Temperature		-25°C~+40°C
Storage Temperature		-25°C~+55°C
Relative Humidity		≤85%(+30°C)
Air Pressure		70Kpa~106Kpa
Colour		Beige and Black
PORT	DIMENSION(DxWxH)	CAPACITY
12 Port	65mm×300mm×265mm	12 fiber
24 Port	94mm×262mm×300mm	24 fiber

### Ordering Information

1. Connector Type: SC, LC, FC, ST
2. Ferrule End-face: PC, UPC, APC
3. Part Number: CV-WMWWUJ-YY WW=Connector Type YY= SM/MM UU= 12 / 24 / 48 (Total Ports)