

# Cavo Technology

## FIBER WALL SOCKET (FWS)

### FEATURES

- Small size, light weight, pleasing in appearance
- Suitable for indoor wall mount
- UL94 V-1 (Sirim tested)
- Cover fasten design makes installation easy

### APPLICATION

- To be used to realize optical fiber to desktop solution.
- To be used at home or working area to accomplish double-core fiber access and port output.
- To be used in the end termination of residential building and villas, to fix and splice with pigtails or FAST Connector.



### SPECIFICATIONS:

Item	Description
Dimension (mm)	H86 x W86 x D25
Weight (Kg)	0.055
Cable diameter (mm)	Φ7 - Φ14
Cable port	2 holes
Max capacity of cable	2 (single fiber)
Application for	Drop cable and indoor cable 3.10 x 2.0mm
Using temperature	-40 - +75
Adaptor	SC/UPC, SC/APC
Insert loss	≤0.20dB (1310nm & 1550nm)
Port output	2 (max)

TM Serial No. : ST OSP 034/18

SIRIM No. : 2014EEA0998, 2015EEA0087

### **Ordering Information :**

1. Connector Type: SC, LC
2. Ferrule End-face: PC, UPC, APC
3. Part Number : CV-FWSUUWW WW = Connector Type UU = 01/02/04 (Total Ports)