

Cavo Technology

PLC SPLITTER FIBER BOX

FEATURES:

- Removable panel design can meet different requirements
- Fit for 19" rack
- Suitable for FC, SC, LC, ST, etc
- The case is made of cold rolled steel sheet, electrostatic spraying, provide 12 & 48 single and double adapter, available for SC, LC, FC, ST.



APPLICATION:

- Local Area Network (LAN)
- Optical Access Network (OAN)
- Data Processing Centers
- Cable Television (CATV)
- Coarse Wavelength Division Multiplexer (CWDM)

MECHANICAL AND ENVIRONMENTAL CHARACTERISTICS:

ITEM	CHARACTERISTICS
Operation Temperature	-25°C~+40°C
Storage Temperature	-25°C~+55°C
Relative Humidity	≤85%(+30°C)
Air Pressure	70Kpa~106Kpa
Colour	Beige and Black

ACCESSORIES:

NO	NAME	QUANTITY
1	Heat Shrinkable Tube	-
2	Nylon Locking Tie Wraps	3 PCS
3	M6 Rack-Screw	4 PCS

Notice: "----"the number is same to fiber cord number

DIMENSION(WxDxH)	CAPACITY
483mm×230mm×1U	1×8
483mm×230mm×1U	1×16
483mm×230mm×1U	1×32

Ordering Information:

1. Connector Type: FC, SC, LC, ST
2. Part Number : CV-RMSP-UU-WWYY WW = Connector Type YY = SM or MM UU: 06, 08, 12, 16, 24 (Total Ports)