

Cavo Technology

FIBER OPTIC PEDESTAL DISTRIBUTION HUB

FEATURES:

- Multiple Installation options, floor mounted or on-top of plinth
- Adapter type: FC, SC, ST, LC
- Capacity up to 24 port. However, others capacity can be customized as required.
- Quick field installation.
- It's design especially for outdoor optical nodes I access network .
- Perfect design for easy fiber cable routing & friendly maintenance of fiber cable.
- Built in compartment for installation of fiber optic splitter. Such as 1x8, 1x16 and so on.
- Suitable for housing, commercial & factory industrial area.

APPLICATION:

- Fiber Optic Telecommunication
- Optical network equipment
- CATV System
- LAN(Local Area Network)



SPECIFICATIONS:

PARAMETERS	VALUE
Working temperature:	-45°C to +85°C
Storage temperature:	-25°C ~+55°C
Relative humidity:	≤85% (+30°C)
Material:	HDPE
Color	Light Green
Dimension	12 Cores - 550 mm x 230 mm (H x D)
	16 - 24 Cores - 700 mm x 310 mm (H x D)

Ordering Information :

1. Connector Type : SC/UPC, FC/UPC, LC/UPC, ST/UPC, SC/APC, FC/APC, LC/APC
2. Cable Type : SM (Single Mode) or MM (Multi Mode)
3. Part Number : CV-PDH-UU-WW WW = Connector Type YY = SM or MM UU: 06, 08, 12, 16, 24 (Total Ports)