

**Motor-driven Superficial Rockwell Hardness Tester
(Digital Gauge)
Model: JG-102S**



(For reference only)

Equipment Usage

It can be used to test the Rockwell hardness of hard alloy, carburized steel, hardened steel, surface quenched steel, hard cast steel, aluminum alloy, copper alloy, malleable cast, mild steel, tempered steel, annealed steel, bearing steel, etc.



Features

- The machine body adopts cast iron structure, which is strong and durable, thus it can be used in various harsh conditions.
- Frictionless loading shaft, high precision testing force
- Test force transformation can be achieved automatically using one press, which facilitates the operation.
- Automatic loading, holding-up of the load and unloading, no human operating error.
- Precision conforms to the Standards of GB/T 230.2, ISO 6508-2 and ASTM E18

Technical Specifications

Model	JG-102S
Measuring range	70-91HR15N, 42-80HR30N, 20-77HR45N, 73-93HR15T, 43-82HR30T, 12-72HR45T
Initial test force	3Kgf (29.42N)
Total test force	147.1, 294.2, 441.3N (15, 30, 45kgf)
Hardness value reading	Digital gauge
Carriage control	Automatic loading / hold up of the load / unloading
Max. Height of test piece	210mm
Depth of throat	160mm
Min. Scale value	0.1HR
Dimension	510 x 220 x 700 (mm)
Package dimension	620 x 490 x 780 (mm)
Power supply	AC 220V/50Hz or AC 110V/60Hz
Net/Gross weight	85kg/100kg



Standard Delivery

Main unit	1 Set
Large flat anvil	1 Pc
Small flat anvil	1 Pc
V- notch anvil	1 Pc
Diamond cone penetrator	1 Pc
Steel ball penetrator ϕ 1.588mm	1 Pc
Steel ball ϕ 1.588mm	5 Pcs
Superficial Rockwell standard blocks	4 Pcs
Power Cable	1 Pc
Screw driver	1 Pc
Auxiliary box	1 pc
Dust cover	1 Pc
Operation manual	1 Pc
Certificate	1 copy

