

Specifications of handing hardware

2. Fuel dispenser hose 4m long and 9 inch short hose



This gasoline delivery hose assembly is a premium solution designed for gravity fed and low pressure pumping installations. Suitable for use with oil and diesel applications, this fuel hose is available in a range of lengths to meet your requirements.

The premium fuel dispensing hose assemblies come with swaged stainless steel full ferrules and BSP hose tails with sealing o rings. As well as in an assembly, this gasoline hose is available by the metre and in coils if you have a large requirement.

Features of the Premium Gravity/Pump Fuel Dispensing Hose:

- Diesel/oil resistant construction
- Anti-static soft wall with NBR cover
- Synthetic textile yarn reinforcement
- ID 19 or 25mm / OD 27 or 34mm
- Temperature -25°C/+70°C
- Different lengths of diesel hose available upon request
- 3/4" assemblies available upon request
- Assemblies c/w 1" BSP hose tails with sealing o rings & swaged stainless steel full ferrules

Oil hose

1. Double walled Fuel Hose
2. HDPE Transparent braided PVC hose

Double walled Fuel Hose

Applications:

It is suitable for delivery such petroleum base and water base as fuel and lubricating oil, a temperature range of -40°C to 121°C (-40°F~+250°F)

Features:

The hose is composed of synthetic rubber layer, wire reinforced reinforcement, and layers designed as hose, and synthetic rubber cover.

Working Temperature : -30°C to +55°C

Double walled Fuel Hose	
Material:	rubber
Color:	blue,black,red.green. white.
Inside:	metal wire
One roll	60 meters
Size	3/4",1"

Hose Picture:



