



Contact clamps	Low Voltage	Overhead lines and cabins
----------------	-------------	---------------------------

Contact clamps



BT322	PE20	S20
ICC 6 kA / 1 s	ICC 5.2 kA / 1 s	ICC 23.8 kA / 1 s
Round conductors \varnothing 2÷22 mm	Screw and nuts with hexagonal head, opening up to 20 mm	Round conductors \varnothing 3÷30 mm
Rods in fiberglass tube	DIN bayonet tangs	DIN bayonet tangs

Contact clamps	Medium Voltage	Overhead lines and cabins
----------------	----------------	---------------------------

Contact clamps



PC332	PC/BM-AL	PC535
ICC 12.7 kA / 1 s	ICC 20 kA / 1 s	ICC 30 kA / 1 s
Round conductors and bars \varnothing 3÷32 mm	Round conductors \varnothing 5÷40 mm; Flat bars 40x60 mm (—); Vertical Bars 12x60 mm (I); 45° slanting bars up to 28 mm thickness (/).	Round conductors \varnothing 5÷35 mm; Flat bars 5x40 mm (—); Bars on horizontal levels 16x40 mm (I);
Clamp holder head	Hexagonal or DIN bayonet tangs	Hexagonal or DIN bayonet tangs

Contact clamps



PF20	PF25	PC2014
ICC 30.9 kA / 1 s	ICC 30.9 kA / 1 s	ICC 13.5 kA / 1 s
Round conductors, bars max 22 mm Spherical fixed point \varnothing 20 mm	Round conductors, bars max 22 mm Spherical fixed point \varnothing 25 mm	Round conductors \varnothing 6 ÷ 35 mm
Hexagonal or DIN bayonet tangs	Hexagonal or DIN bayonet tangs	Hexagonal or DIN bayonet tangs