



Contact clamps	High Voltage	Overhead lines and substations
-----------------------	---------------------	---------------------------------------

Pinze di contatto



PC560/A	PC560/D	PC560/CH
ICC 41 kA / 1 s	ICC 41 kA / 1 s	ICC 41 kA / 1 s
Round conductors Ø 5+60 mm	Round conductors Ø 5+60 mm	Round conductors Ø 5+60 mm
Ring tangs	DIN bayonet tangs	Hexagonal tangs

Contact clamps



PC560/C	PC120/C	PC-BMG/C
ICC 41 kA / 1 s	ICC 40.7 kA / 1 s	ICC 30.7 kA / 1 s
Round conductors Ø 5+60 mm	Round conductors Ø 20+120 mm	Round conductors Ø 20+120 mm Flat bars up to 90x100 mm (—); Bars on horizontal levels up to 20x110 mm (▮); 45° slanting bars up to 50x120 mm (▽)
Hexagonal and bayonet DIN tangs	Hexagonal and bayonet DIN tangs	Hexagonal and bayonet DIN tangs

Ground clamps	Low Medium High Voltage	Overhead lines and cabins
----------------------	--------------------------------	----------------------------------

Ground clamps



MT33	MT40	MT50
ICC 40 kA / 1 s	ICC 41 kA / 1 s	ICC 41 kA / 1 s
Round conductors and flat bars up to 33 mm	Round conductors and flat bars up to 40 mm	Round conductors and flat bars up to 50 mm
Steel Handle	Steel Handle	Steel Handle