



For Detectors and Disconnection

Low Medium High Voltage

Lines and substations

## Telescopic insulating rods in 3 elements for voltage detectors and hooks for switches disconnection

Telescopic insulating rods in 3 elements for external and internal use made of different type of tubes:

- P in polyester resin reinforced by fiberglass, Ø 40 and 32 mm
- PR in polyester resin reinforced by fiberglass and filled by closed cells polyurethane foam, Ø 24 mm
- PE in epoxy resin reinforced by fiberglass, certified IEC 61235, Ø 48 and 40 mm
- PV in vinylester resin reinforced by fiberglass, certified IEC 61235, Ø 40 and 32 mm
- PVR in vinylester resin reinforced by fiberglass and filled by closed cells polyurethane foam, IEC 60855-1, Ø 32 mm

Length on demand, complete of:

- suitable top fitting for the maneuvering of contact clamps or voltage detectors;
- insulating closing cap;
- hand guard.



P3/380U-TEL PE2-PVR/520U-TEL

Code	Composition	Length	Conformity
<b>P3/380FA-TEL</b>	P Ø 40 and 32 – PR Ø 24	1.6 – 3.8 m	-
<b>P3/380U-TEL</b>	P Ø 40 and 32 – PR Ø 24	1.6 – 3.8 m	-
<b>P3/380EF-TEL</b>	P Ø 40 and 32 – PR Ø 24	1.6 – 3.8 m	-

Code	Composition	Length	Conformity
<b>PE2-PV/300FA-TEL</b>	PE Ø 48 and 40 - PV Ø 32	1.16 – 3 m	IEC 61235
<b>PE2-PV/300DIN-TEL</b>	PE Ø 48 and 40 - PV Ø 32	1.16 – 3 m	IEC 61235
<b>PE2-PV/300EF-TEL</b>	PE Ø 48 and 40 - PV Ø 32	1.16 – 3 m	IEC 61235
<b>PE2-PV/300U-TEL</b>	PE Ø 48 and 40 - PV Ø 32	1.16 – 3 m	IEC 61235

Code	Composition	Length	Conformity
<b>PE2-PVR/520FA-TEL</b>	PE Ø 48 and 40 - PVR Ø 32	1.9 – 5.2 m	IEC 60855-1
<b>PE2-PVR/520DIN-TEL</b>	PE Ø 48 and 40 - PVR Ø 32	1.9 – 5.2 m	IEC 60855-1
<b>PE2-PVR/520EF-TEL</b>	PE Ø 48 and 40 - PVR Ø 32	1.9 – 5.2 m	IEC 60855-1
<b>PE2-PVR/520U-TEL</b>	PE Ø 48 and 40 - PVR Ø 32	1.9 – 5.2 m	IEC 60855-1

### Attacks



**EF**



**U**



**FA**

### Maneuvering metallic hooks



**GSF**



**GSH**



**GS**



**GSU**