



Voltage detectors	DC	Railway lines
-------------------	----	---------------

Code: **RTC1800/FIL**



DC voltage electronic detector with visual and acoustic signals for use on trolley-bus lines

Range	385 + 1800 V c.c.
-------	-------------------



- Suitable for indoor and outdoor use.
- Double indication of operative voltage presence: intermittent acoustic and flashing of **red LEDs**.
- The absence of operative voltage is indicated by **green LEDs** permanent on.
- The lighting of the **orange LED** is the indication of low battery.
- **Built-in self-control check** for testing the accurate working of the voltage detector before use.
- Cylindrical box made of ABS.
- Hook shape metallic contact probe, **360° swivel type**.
- **Universal U** end fitting splined for connection onto the head of to the insulating rod.
- Supply: alkaline battery 9 V.
- Electrolytic copper cable covered by thermoplastic rubber sheath for connection to the neutral conductor. Section **1 mm²**, length **2 m** (different lengths on demand).
- Metallic case.
- **2** Insulating rods made of in resin tube reinforced by fiberglass, total length of one rod **4 m** in 2 elements (different lengths on demand) connecting between them by quick coupler. The first rod is complete with a metallic hook contact probe, the second one with fitting for the voltage detector.
- Heavy waterproof fabric containing the insulating rods.

Electrical continuity	DC	Railway lines
-----------------------	----	---------------

Code: **WI33-120**

Portable device for electrical continuity between rails



- **2** forged brass ground clamps suitable for clamping on the lower part of the rail.
- Extraflexible electrolytic copper cable covered by transparent rubber sheath. Section **120 mm²**, length **1.5 m** (different lengths on demand).
- Rigid plastic case.