



STATIC WEATHER SENSOR "EOLOS-IND"

Wind · Air temperature · Rel. humidity · Barometric pressure
5 parameters plus dew point!

The perfect weather sensor...

for a wide range of applications, especially for use under harsh environmental conditions.

The integrated sensors in the weather module are measuring the ambient parameters with high precision. The compact construction of the static measuring system and the space saving, robust housing make the sensor extremely reliable and durable.

- very high wind velocities up to 85 m/s measurable!
- without moving measuring elements
- 5 weather parameters measurable
- lamella shelter for accurate measurements of the temperature-humidity sensor
- optimal heatable
- easy installation, easy to maintain

land applications under any conditions •
wind turbines • railway line monitoring •
traffic meteorology • weather services and
Offices of the Environment • chemical and
industrial facilities • power plants, sewage
plants and landfills



Professional Line	(1643)	Static Weather Sensor EOLOS-IND H	Id-No. 00.16430.010 002
<u>Parameters:</u>			
Wind direction:	Meas. range:	Accuracy:	Resolution:
	0...360°	± 3°	1°
Wind speed:	0.1...85 m/s	± 0.5 m/s ± 5 % of the meas. value	0.1 m/s
Air temperature:	-40...+70 °C	± 0.8 °C (v > 2 m/s)	0.1 °C
Relative humidity:	0...100 % r. h.	± 3 % (10...90 %) • ± 4 % (0...100 %)	0.5 r. h.
Barometric pressure:	600...1100 hPa	± 2 hPa (-30...+70 °C)	0.1 hPa
Range of application:	temperature -40...+70 °C heated • wind speed 0...100 m/s • 0...100 % r. h.		
Protocols:	NMEA 0183 • WIMWV • WIMHU • WIMMB • WIMTA		
Interface:	serial · RS 422/ talker • baud rate 4800 • 1 Hz (meas. cycle of 10 Hz) • 8 N 1		
Supply voltage:	24 VDC (-22 % / +34 %) • max. 2.5 A • heating: 24 VDC/ 70 W (max. 3 A) · electr. controlled		
Housing:	aluminium · anodized · IP 66		
Dimensions/ Weight:	H 382 mm · Ø 120 mm · mast adapter Ø 50 mm for mounting on standard pipe • 2.5 kg		
<u>Version:</u>	(1643)	Static Weather Sensor EOLOS-IND unheated	Id-No. 00.16430.000 002
		Range of application: -30...+70 °C · under non-icing conditions	
<u>Accessory:</u>	Cable 10 m · 12-pole bayonet plug · ready-made		
32.16420.066 100			
<u>Options:</u>	Visualisation and evaluation software MeteoWare-CS3		
36.09340.000 000	Data logger met[LOG]		
00.95800.010 000			
00.14742.401 002	Display unit METEO-LCD/IND		