

WIRSB-CL4-NX

Safety Trolley Bag

Compact and portable kit for safety works from electric risks CLASS 4 for tensions up to 36 kV

Safety suitcase:

- Nylon suitcase with 30 % of fiber glass.
Trolley type with extensible handle and wheels for transport.
Certified water-proof: **IP67**
Dimensions: 687 x 528 x 376 mm.



Voltage detector	RMT1030 Electronic capacitive detector to detect voltage presence/absence on MV lines and installations by visual and acoustic signals, range 3kV ÷ 60 kV (specific range of tension must be indicate in the order). Certified in conformity with the International Standard IEC 61243-1 .
Safety hook	Steel hook covered by plastic sheath.
Insulating Rod	P3/150EF-TEL Insulating telescopic rod in three elements, extended length 1.5 m.

Dielectric Gloves	WIG4 Maximum voltage use 36 kV. Dielectric gloves with bag; certified Personal Protection Equipment, in compliance with the International Standard IEC 60903 .
Dielectric Boots	Resistant dielectric boots up to 20 kV certified EN 50321-EN20345 , ASTM F-1117
Insulating Rubber Mat	WI4/100-0,6 Insulating rubber mat certified in conformity with the International Standard IEC 61111 , CLASS 4, dimensions 100x60 cm. Maximum operating voltage 36 kV.
Insulating Cable Cutter	WI/TRC Insulating Shear for cable cutting with handles in epoxy resin reinforced by fiberglass. (tube of the handles certified IEC 61235)
Accessories	<ul style="list-style-type: none"> • Delimitation tape • Talc • Instructions