

Wöhler VIS 250 Visual Inspection Camera

TECHNICAL DATA

Monitor

Dimensions housing.....176 x 114 x 32 mm
 TFT-display7" / 16:9 format
 Video outRCA signal
 Weight.....400 g
 Power supply.....Space for 2 rechargeable batteries, each 12 V or via power pack
 Battery operating time.....Max. 2 rechargeable batteries, each 120 mins. = 4 h
 (battery status in display)

Miniature camera head, color Ø 26 mm

Type1/3" COLOR CMOS
 Resolution420 lines
 Pixels.....768 x 576 (PAL), 656 x 492 (NTSC)
 Light sensitivity0.5 Lux
 Lensf = 2.3 mm, F = 2.5
 Viewing angle.....115°
 Light source12 white LEDs
 Degree of protectionWaterproof to IP 68
 DimensionsØ 26 mm x 38 mm
 Weight.....240 g
 Operation temperature.....0...40 °C, RH 95 % MAX
 Storage temperature.....-20...50 °C, RH 95 % MAX
 Transmitter frequency.....8.9 kHz

Distance measurement

Wöhler VIS 200/250 Electronic meter counter

Plastic case

Dimensions.....51 x 43 x 17 cm (L x W x H)
 Weight.....7 kg

Memory (Wöhler VIS 250)

Recording2 GB SD card (2,5 h recording capacity)
 InterfaceMini USB port

Locator sender

Transmitter frequency8.9 kHz

Locator receiver

Display.....Graphic visualization of transmitted position
 Output impedance
 Headphones32 Ohm
 Power supply.....3.7 V Li-Ion rechargeable battery
 Operating temperature.....0...40 °C
 Storage temperature.....-10 °C...40 °C
 Weight.....605 g
 Dimensions32 x 14 x 7 cm (L x W x H)

¹⁾ Excepted from this: Opening of the housing, inappropriate handling; For further information please see our guarantee guidelines