

Cisco 95 Series Unmanaged Switches

Affordable, Easy-to-Use Switches for Small Business Networks, with Zero Configuration Required

Highlights

- Affordable 10/100/1000-Mbps speeds for even the most bandwidth-hungry applications
- 5- to 24-port models that are desktop or rack mountable
- Integrated support for traffic prioritization, loop detection, cable diagnostics, and more
- Works right out of the box: plug and play and no setup

Product Overview

Give your office network a boost of speed and performance at a low price that takes almost no time to set up. Easily build a highly reliable network to connect your computers, printers, copiers, and other office equipment. If your business is like most small companies, you do not have an IT staff to set up your network for you. Now you can have a high-performance, business-class office network that just works, right out of the box, with the Cisco® 95 Series Unmanaged Switches. Users, workgroups, labs, departments, or growing offices can now deliver large amounts of multimedia, image, and video information across the network in almost no time.

Cisco 95 Series Unmanaged Switches deliver basic network connectivity and reliability for small businesses that is easy on the budget and without all the complexity. These switches provide all of the features, expandability, and investment protection you expect from Cisco, with no installation software and nothing to configure. Just plug it in, connect your computers and other business equipment, and get to work.

Cisco 95 Series Unmanaged Switches (Figure 1), part of the Cisco Small Business networking solutions, are a line of unmanaged switches that provide wire-speed Fast Ethernet and Gigabit Ethernet connectivity to connect your small business office. Available in desktop and rack-mount models, these switches are designed to suit any office space with basic network needs and to optimize power efficiency. They use less power and provide the robust, reliable connectivity your business demands, as well as support for advanced features such as quality of service (QoS), loop detection, and cable diagnostics, all in a switch that you can set up yourself in minutes. A business-class, affordable network solution, Cisco 95 Series switches bring the proven reliability and investment protection of Cisco networking solutions to your small business.

Figure 1. Cisco 95 Series Unmanaged Switches



Features

Cisco 95 Series switches provide an easy-to-use solution for your small business network. They offer:

- **Ease of use:** Cisco 95 Series switches work right out of the box, with no software to install and nothing to configure. Each switch port independently sets itself for the optimal speed and determines whether to run in half- or full-duplex mode automatically. As a standards-based Cisco solution, Cisco 95 Series switches are also designed to immediately accommodate all of the devices in your network, including:
 - Support for 10 megabits per second (Mbps), 100 Mbps, and up to 1 gigabit per second (1000 Mbps) devices in the same network
 - Automatic cable detection, so you do not have to worry about using the wrong cable type
 - Compatibility with network devices from other vendors
- **Simple setup:** Designed for small office spaces, Cisco 95 Series switches are available in both compact desktop and rack-mount models. The desktop models offer a wall-mount option for discreet mounting under a desk or on the wall of an office or conference room.
- **High performance:** Cisco 95 Series switches deliver the performance you need to run your business applications, including bandwidth-intensive video services, and avoid slow and sluggish networks. They support Gigabit Ethernet speeds, unlocking a new level of capacity and performance in your business network and letting you transfer large files in seconds.
- **Reduced energy costs:** Cisco 95 Series switches are designed to help conserve energy by optimizing power use without compromising performance, which protects our environment and reduces your energy costs. In addition, they support the Energy Efficient Ethernet (IEEE 802.3az) standard, which reduces energy consumption by monitoring the amount of traffic on an active link and putting the link into a sleep state during quiet periods. Most of the switches have no fans, so they run silently and unobtrusively while lowering energy costs.
- **Support for advanced technologies:** All switches include advanced Cisco traffic-handling features to keep your applications running at peak performance. Integrated QoS intelligence on all models automatically prioritizes delay-sensitive services such as voice or video to improve your network's performance. Loop detection helps discover loops in the network that you might have accidentally created, thus avoiding broadcast storms that will bring your network to a stall. Cable diagnostics help to quickly identify and troubleshoot network cabling faults and issues. Fast store-and-forward switching identifies damaged packets and prevents them from being passed on through the network. All of these features run automatically, with no management or configuration required.

- **Peace of mind:** Cisco 95 Series switches deliver the rock-solid reliability you expect from a Cisco switch. The solution has been rigorously tested to make sure of optimal uptime and performance. In addition, the limited lifetime hardware warranty provides peace of mind.

Specifications

Table 1 lists the specifications, package contents, and minimum requirements for the Cisco 95 Series.

Table 1. Specifications for Cisco 95 Series Switches

Specifications	Description
Standards	IEEE 802.3 10BASE-T Ethernet, IEEE 802.3u 100BASE-TX Fast Ethernet, IEEE 802.3ab 1000BASE-T Gigabit Ethernet, IEEE 802.3z Gigabit Ethernet, IEEE 802.3x Flow Control, 802.1p priority, Energy Efficient Ethernet
Cabling type	Category 5e or better
LED indicators	System/PWR, link/activity, 100M*, cable diagnostics, loop detection, gigabit,* mini-GBIC* *if present
Physical Interfaces	
Ports	10/100/1000 Ethernet, power port for AC adapter or power cord
Power supply	SF95D-05, SF95D-08: DC 12V, 500mA SF95D-16, SG95D-08, SG95D-05: DC 12V, 1.0A SF95-24, SG95-16, SG95-24: 110-240VAC, 50-60 Hz, internal, universal
Lock slot	Slot for Kensington lock
Physical Specifications	
Physical dimensions (W x D x H)	SF95D-05: 110x30x75 mm SF95D-08: 160x30x90 mm SF95D-16: 160x43.5x90 mm SF95-24: 279.4x44.45x170 mm SG95D-05: 110x30x100 mm SG95D-08: 160x30x103.5 mm SG95-16: 279.4 x 26 x 110 mm SG95-24: 279.4x44.45x170mm
Weight	SF95D-05: 0.47 lb. (0.22 kg) SF95D-08: 0.83 lb. (0.38 kg) SF95D-16: 1.03 lb. (0.46 kg) SF95-24: 2.91 lb. (1.32 kg) SG95D-05: 0.70 lb. (0.32 kg) SG95D-08: 0.94 lb. (0.43 kg) SG95-16: 3.15 lb. (2.13 kg) SG95-24: 3.59 lb. (1.63 kg)
Ports	SF95D-05: 5 RJ-45 connectors for 10BASE-T/100BASE-TX SF95D-08: 8 RJ-45 connectors for 10BASE-T/100BASE-TX SF95D-16: 16 RJ-45 connectors for 10BASE-T/100BASE-TX SF95-24: 24 RJ-45 connectors for 10BASE-T/100BASE-TX SG95D-08: 8 RJ-45 connectors for 10BASE-T/100BASE-TX/1000BASE-T ports SG95-16: 16 RJ-45 connectors for 10BASE-T/100BASE-TX/1000BASE-T ports SG95-24: 24 RJ-45 connectors for 10BASE-T/100BASE-TX/1000BASE-T ports with 2 combo mini-GBIC slots All units: automatic medium dependent interface (MDI) and MDI crossover (MDI-X); auto-negotiated port for connecting 10-, 100-, 1000-Mbps devices
Fan/fanless models	All models have no fans and are fanless

Specifications	Description
Performance	
Switching capacity	SF95D-05: 1 Gbps SF95D-08: 1.6 Gbps SF95D-16: 3.2 Gbps SF95-24: 4.8 Gbps SG95D-05: 10 Gbps SG95D-08: 16 Gbps SG95-16: 32 Gbps SG95-24: 48 Gbps
Forwarding capacity	Forwarding rate in million packets per second (mpps) (based on 64-byte packets): SF95D-05: 0.74 mpps SF95D-08: 1.4 mpps SF95D-16: 1.4 mpps SF95-24: 3.6 mpps SG95D-05: 7.4 mpps SG95D-08: 11.9 mpps SG95-16: 23.8 mpps SG95-24: 35.7 mpps
Capabilities	
Head-of-line (HOL) blocking	HOL blocking prevention
Jumbo frame	9216 bytes
Quality of service (QoS)	802.1p priority based, hardware queues, priority queuing and weighted round-robin (WRR)
Loop detection	Helps discover loops in the network to avoid broadcast storms
Cable diagnostics	Quickly identify and troubleshoot network cable faults and/or shorts
Mounting and Physical Security	
Mounting options	Desktop or rack mount
Physical security lock	Kensington lock slot
Environmental	
Compliance/certifications	UL (UL 60950), CSA (CSA 22.2), CE mark, FCC Part 15 (CFR 47) Class A, FCC Class B* *select models
Operating temperature	32° to 104°F (0° to 40°C)
Storage temperature	-4° to 158°F (-20° to 70°C)
Operating humidity	10% to 90%, relative, noncondensing
Storage humidity	5% to 90%, relative, noncondensing
Package Contents	
<ul style="list-style-type: none"> • Cisco 95 Series switch • Power cord/power adapter • Mounting hardware 	
Minimum Requirements	
<ul style="list-style-type: none"> • Devices supporting 802.3 Ethernet, 802.u Faster Ethernet, or 802.3ab Gigabit Ethernet • Cat5 or better Ethernet cable • Network interface card for each computer 	
Warranty	
Cisco 95 Series switch	Limited lifetime

Ordering Information

Table 2 gives ordering information for the Cisco 95 Series Unmanaged Switches.

Table 2. Ordering Information for Cisco 95 Series Unmanaged Switches

Part Number	Description
SF95D-05	Cisco SF95D-05 - 5-Port 10/100 Desktop Switch
SF95D-08	Cisco SF95D-08 8-port 10/100 Desktop Switch
SF95D-16	Cisco SF95D-16 16-port 10/100 Desktop Switch
SF95-24	Cisco SF95-24 24-Port 10/100 Switch
SG95D-05	Cisco SG95D-05 5-port Gigabit Desktop Switch
SG95D-08	Cisco SG95D-08 8-Port Gigabit Switch
SG95-16	Cisco SG95-16 16-Port Gigabit Switch
SG95-24	Cisco SG95-24 Compact 24-port Gigabit Switch + 2 Mini GBIC Ports 1U

Cisco Limited Lifetime Warranty for Cisco Small Business Products

This Cisco Small Business product comes with a limited lifetime hardware warranty. Product warranty terms and other information applicable to Cisco products are available at www.cisco.com/go/warranty.

Services for Small Business

Reduce downtime with fast, expert technical support and flexible hardware coverage. Cisco Services improve network availability and help you get the most value from your Cisco products. Service plans for your Cisco Small Business products provide more support than a product warranty. A warranty protects you against product defects, and a majority of support calls are unrelated to faulty materials or manufacturing. Most callers ask about product features, technical problems, or how to expand their network.

Cisco offers an unlimited number of calls and no restrictions on call duration, so you can get the help you need and the most from your Cisco product.

For more information about Cisco Services, see www.cisco.com/go/sbs.

For More Information

For more information about Cisco Small Business products and solutions, visit www.cisco.com/smallbusiness



Americas Headquarters
Cisco Systems, Inc.
San Jose, CA

Asia Pacific Headquarters
Cisco Systems (USA) Pte. Ltd.
Singapore

Europe Headquarters
Cisco Systems International BV Amsterdam,
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: www.cisco.com/go/trademarks. Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)