



ZyWALL USG110/210/310

Unified Security Gateway

More and more people are relying on smart devices and cloud-based applications for business communications. This means that high network availability is critical for business continuity, more WiFi is demanded in the workplace, and traditional regulatory measures for application usage are obsolete. Without an effective solution to control, optimize and block social, productivity and other Web applications, SMBs risk losing work productivity and exposing company networks to new Web threats.

The ZyWALL USG110/210/310 are UTM Firewalls designed to meet the mobility, anti-malware and policy enforcement challenges in SMBs. The integrated WLAN controller offers easy WLAN scalability for the growing demand for WiFi; while WAN and VPN load balancing and failover ensures non-stop business communications. ZyXel USGs offer industry-leading Anti-Virus, Anti-Spam, Content Filtering 2.0 and Application Patrol technology for effective application optimization and comprehensive network protection.



Unified Security Firewall gateway Firewall for small and medium-sized businesses



Complete network protection with firewall, Anti-Virus, Anti-Spam, Content Filtering 2.0, IDP, Application Patrol



Robust SSL, IPSec and L2TP over IPSec VPN connectivity and VPN high availability (HA)



Unified security policy



Cloud helper provide friendly firmware upgrade.



Device HA Pro ensures smart handover



Hotspot management is supported



Facebook WiFi, Intelligence social media authentication



OneSecurity

Benefits

Impregnable protection and optimization

ZyWALL USG110/210/310 thoroughly protects networks with industry-leading firewall, Anti-Malware/Virus, Anti-Spam, Content Filtering, IDP, and Application Patrol functionality. Regulate unauthorized use of Web applications over your network, such as Facebook, Google apps, and Netflix, among others. Zyxel security measures are enhanced with SSL Inspection, blocking threats hidden in SSL-encrypted connections while facilitating deeper policy enforcement. Furthermore, newly improved Content Filtering 2.0 enhances HTTPS Domain Filter, Browser SafeSearch, and Geo IP Blocking for an array of security enhancements to ensure clean Web connections.

Powerful, robust and always-online

ZyWALL USG Series delivers high-access quality to help businesses satisfy the demand for always-online communications. For internal deployments, the ZyWALL USG Series provides active-passive High-Availability (HA) service to support device or connection failover. With Device HA Pro service, the ZyWALL USG Series also supports instant failover, so connections are always maintained when a failover event occurs. For external deployments, the ZyWALL USG Series features multi-WAN load balancing/failover and a comprehensive mobile broadband USB modem support list for WAN backup operations. The ZyWALL USG Series also supports IPSec load balancing and failover, providing additional resilience for mission-critical VPN failover with VTI Interface deployments.

Multi-element service access

The ZyWALL USG Series helps SMBs meet the connectivity demands of an ever-growing legion of wireless devices. Each gateway in the series is integrated with a WLAN controller that enables users to manage up to 34 APs through a centralized user interface. Businesses can now easily scale up WLAN and provide WiFi in multiple areas, like meeting rooms and guest reception areas. Hotspot Management features — such as Billing System, Walled Garden, Multiple Authentications, 3rd Party Social Login, and User Agreement — to give businesses with a single unified solution for all required functionality.

Swift and secure firmware upgrades

Locating firmware updates — not to mention identifying correct versions for your device and managing their installation — can be a complex and confusing ordeal. The ZyWALL USG Series solves this with its new Cloud Helper service. Cloud Helper provides a simple step to look for up-to-date firmware information. New firmware is immediately made available upon release from our official database to ensure its authenticity and reliability.

Zyxel One Network experience

Aiming for relieving our customers from repetitive operations of deploying and managing a network, Zyxel One Network is designed to simplify the configuration, management, and troubleshooting, allowing our customers to focus on the business priorities. Zyxel One Network presents an easy-to-use tool, Zyxel One Network Utility (ZON Utility), to realize speed network setup. Zyxel Smart Connect allows Zyxel networking equipment to be aware and recognize each other and further facilitating the network maintenance via one-click remote functions such as factory reset or power cycling. Zyxel One Network redefines the network integration across multiple networking products from switch to WiFi AP and to Gateway.

Stay secure and up-to-date with OneSecurity

Zyxel provides frequent and timely updates in response to the latest security threats and advisories through OneSecurity — our free online service portal. OneSecurity offers informative network security resources and the know-how to assist businesses and IT administrators in keeping their network operations safe in the digital age. Information and resources can be found with one click via the GUI of ZyWALL USG Series and VPN Series products. IT staff can quickly and easily catch up on the latest threats, and then proceed to walkthroughs and troubleshooting protocols with the help of easy-to-follow FAQs — all provided to help users secure their networks and simplify management of our UTM products.

ZyWALL USG Series Quick Finder



Model	USG40/40W	USG60/60W	USG110	USG210	USG310	USG1100	USG1900
Description	SB		SMB			SMB	
Firewall throughput (Mbps)	400	1,000	1,600	1,900	5,000	6,000	7,000
Max. concurrent sessions	50,000	100,000	150,000	200,000	500,000	1,000,000	1,000,000
UTM throughput (AV and IDP) (Mbps)	50	90	450	500	550	650	710
IDP throughput (Mbps)	95	150	590	660	900	1000	1200
AV throughput (Mbps)	50	90	450	500	550	650	710
Amazon VPC^{*1}	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Device HA Pro	-	-	Yes ^{*2}	Yes ^{*2}	Yes ^{*2}	Activate once registered	Activate once registered
Hotspot Management^{*2}	-	-	Yes	Yes	Yes	Yes	Yes
Facebook WiFi	Yes	Yes	Yes	Yes	Yes	Yes	Yes

*1: ZyWALL/USG still be able to support by CLIs

*2: With Zyxel service license to enable or extend the feature capacity

Subscription Services

The ZyWALL USG110/210/310 provides a complete feature set to perfectly fit different business requirements as well as to enable the maximum performance and security with an all-in-one appliance. Comprehensive network modularity also empowers IT professionals to customize the system to meet their individual needs.

*: Hotspot Management supports for USG310/1100/1900 in firmware ZLD4.20 or later, and for USG110/210 in firmware ZLD4.25 or later.



Anti-Virus



Anti-Spam



Intrusion Detection
& Prevention



Application Patrol



Content Filtering 2.0



Hotspot
Management



Device HA Pro

Feature Highlights

Multi-WAN & Mobile Broadband

The ZyWALL USG Series provides non-stop Internet uptime with multi-WAN and mobile broadband support. Multi-WAN works with two or more Ethernet WAN connections for active-active WAN load balancing or active-passive failover. Comprehensive mobile broadband USB modems are also supported for WAN backup.

Unified Security Policy

Unified security policy offers object-based management and a unified configuration interface for firewall and all security-related policies. Users can easily apply all policy criteria to every UTM feature, reduce configuration time, and get more streamlined policy management.

Cloud Helper

Cloud helper could provide the friendly firmware upgrade, user don't need to worry where and how to receive the latest firmware information and file. And the few steps to download and update the firmware directly, it's very convenient to save the setting time.

Zyxel One Network Utility

The ZON utility features smart functions to assist network management for administrators to perform batch firmware upgrade for devices, remote reboot of devices such as ceiling APs or redirect to device GUI for further configuration with just a click. These troublesome but necessary management tasks can now be easily done through just one platform for WiFi APs, switches and gateways.

SSL Inspection

SSL inspection enables the ZyWALL USG Series to provide not only comprehensive security, but also deeper policy enforcement. It enables the USG's Application Patrol, IDP, Content Filtering 2.0 and Anti-Virus to inspect traffic in SSL encrypted connections and block threats that usually go unseen.

Robust VPN

ZyWALL USG Series support high-throughput IPsec, L2TP over IPsec and SSL VPN for a wide range of site-to-client and site-to-site VPN deployments. Reinforced with the advanced SHA-2 authentication, the ZyWALL USG Series provide the most secure VPN for business communications.

Integrated WLAN Controller

The integrated WLAN controller supports CAPWAP, and enables centralized authentication and access management of multiple APs in the network. The ZyWALL USG Series can manage 2 APs by default, and up to 34 APs with license upgrade.


PCI DSS Compliance

The ZyWALL USG Series conform Payment Card Industry Data Security Standard (PCI DSS) is a global standard for data security of cardholder data that affects a very broad group of businesses. The PCI DSS Compliance applies to all entities involved in processing of payment cards, such as merchants, card issuers, processors, and service providers, as well as those that process, transmit, or store cardholder data.

Application Diagram


Anti-malware protection and application optimization

- Enabling Anti-Virus, Anti-Spam and Intrusion Prevention, business networks gain deep, extensive protection against all types of malware threats
- Content Filtering 2.0 enables businesses to deny access to Websites that are malicious or not business-related
- Application Patrol technology not only enable businesses to block or throttle non-productive Web applications, but also optimize Web applications that increase productivity



VPN application

- Branch offices, partners and home users can deploy ZyWALL USG Series for site-to-site IPSec VPN connections
- Branch offices can additionally deploy IPSec VPN HA (load balancing and failover) for always online VPN connectivity
- Remote users can securely access company resources with their computers or smartphones via SSL, IPSec and L2TP over IPSec VPN
- The headquarter ZyWALL USG Series can also establish an IPSec VPN connection with Amazon VPC for secured access to a variety of cloud-based applications






Hotspot Management

- High speed internet access
- Tier of service
- Log record for regulatory compliance
- Premium security control
- Various Network access control (free or paid access, social login)

*: Hotspot Management supports for USG310 ZLD4.20 or later, and for USG110/210 in Firmware ZLD4.25 or later.

Specifications

Model	USG110	USG210	USG310
Product photo			
Hardware Specifications			
Interfaces	4 x LAN/DMZ, 2 x WAN, 1 x OPT	4 x LAN/DMZ, 2 x WAN, 1 x OPT	8 x GbE(configurable)
USB ports	2	2	2
Console port	Yes (DB9)	Yes (DB9)	Yes (DB9)
Rack-mountable	Yes	Yes	Yes
Fanless	-	-	-
System Capacity & Performance¹			
SPI firewall throughput (Mbps) ²	1600	1,900	5000
VPN throughput (Mbps) ³	400	500	650
IDP throughput (Mbps) ⁴	590	660	900
AV throughput (Mbps) ⁴	450	500	550
UTM throughput (AV and IDP) ⁴	450	500	550
Max. TCP concurrent sessions ⁵	150,000	200,000	500,000
Max. concurrent IPsec VPN tunnels ⁶	100	200	300
Concurrent SSL VPN users (default/max.) ⁷	25 / 150	35/150	50/150
VLAN interface	16	32	64
Concurrent devices logins (default/max.) ^{7,8}	200/300	200/300	500 / 800
WLAN Management			
Managed AP number (default/max.) ⁷	2/34	2/34	2/34
Security Service			
Anti-Virus (AV) ⁷	Yes	Yes	Yes
Intrusion Detection and Prevention (IDP) & Application Patrol ⁷	Yes	Yes	Yes
Anti-Spam ⁷	Yes	Yes	Yes
Content Filtering (CF 2.0) ^{7,9}	Yes	Yes	Yes
Key Features			
VPN	IKEv2, IPsec, SSL, L2TP/IPsec	IKEv2, IPsec, SSL, L2TP/IPsec	IKEv2, IPsec, SSL, L2TP/IPsec
SSL (HTTPS) inspection	Yes	Yes	Yes
EZ Mode	-	-	-
Hotspot Management ⁷	Yes	Yes	Yes
Ticket printer support ¹⁰ / Support Q'ty (max.)	Yes (SP350E) / 10	Yes (SP350E) / 10	Yes (SP350E) / 10
Amazon VPC	Yes	Yes	Yes
Facebook WiFi	Yes	Yes	Yes
Device HA Pro	Yes ⁷	Yes ⁷	Yes ⁷
Link Aggregation (LAG)	-	-	Yes

Model	USG110	USG210	USG310	
Power Requirements				
Power input	12V DC, 3.33 A max.	12V DC, 3.33 A max.	100 – 240V AC, 50/60 Hz, 1.3 A max.	
Max. power consumption (watt)	37.0	37.0	58.5	
Heat dissipation (BTU/hr)	126.25	126.25	199.61	
Physical Specifications				
Item	Dimensions (WxDxH) (mm/in.)	300 x 188 x 44/ 11.81 x 7.4 x 1.73	300 x 188 x 44/ 11.81 x 7.4 x 1.73	430 x 250 x 44/ 16.93 x 9.84 x 1.73
	Weight (Kg/lb.)	2/4.4	2/4.4	3.3/7.28
	Packing Dimensions (WxDxH) (mm/in.)	351 x 149 x 243/ 13.82 x 5.98 x 9.65	351 x 152 x 245/ 13.82 x 5.98 x 9.65	519 x 392 x 163/ 20.43 x 15.43 x 6.42
	Weight (kg/lb.)	3.264/7.20	3.264/7.20	4.8/10.58
Included accessories	<ul style="list-style-type: none"> • Power adapter • Power cord • Rack mounting kit 	<ul style="list-style-type: none"> • Power adapter • Power cord • Rack mounting kit 	<ul style="list-style-type: none"> • Power cord • Rack mounting kit 	
Environmental Specifications				
Operating	Temperature	0°C to 40°C (32°F to 104°F)	0°C to 40°C (32°F to 104°F)	0°C to 40°C (32°F to 104°F)
	Humidity	10% to 90% (non-condensing)	10% to 90% (non-condensing)	10% to 90% (non-condensing)
Storage	Temperature	-30°C to 70°C (-22°F to 158°F)	-30°C to 70°C (-22°F to 158°F)	-30°C to 70°C (-22°F to 158°F)
	Humidity	10% to 90% (non-condensing)	10% to 90% (non-condensing)	10% to 90% (non-condensing)
MTBF (hr)	787,109.3	787,109.3	560,811.5	
Certifications				
EMC	FCC Part 15 (Class A), CE EMC (Class A), C-Tick (Class A), BSMI	FCC Part 15 (Class A), CE EMC (Class A), C-Tick (Class A), BSMI	FCC Part 15 (Class A), CE EMC (Class A), C-Tick (Class A), BSMI	
Safety	LVD (EN60950-1), BSMI	LVD (EN60950-1), BSMI	LVD (EN60950-1), BSMI	

Note:

*: This matrix with firmware ZLD4.31 or later.

*1: Actual performance may vary depending on network conditions and activated applications

*2: Maximum throughput based on RFC 2544 (1,518-byte UDP packets).

*3: VPN throughput measured based on RFC 2544 (1,424-byte UDP packets).

*4: AV and IDP throughput measured using the industry standard HTTP performance test (1,460-byte HTTP packets). Testing done with multiple flows.

*5: Maximum sessions measured using the industry standard IXIA IxLoad testing tool.

*6: Including Gateway-to-Gateway and Client-to-Gateway.

*7: With Zyxel service license to enable or extend the feature capacity.

*8: This is the recommend maximum number of concurrent logged-in devices.

*9: SafeSearch function in CF2.0 need to enable SSL inspection firstly and not for small business models.

*10: With Hotspot Management license support.

Features Set

Software Features

Firewall

- ICSA-certified corporate firewall
- Routing and transparent (bridge) modes
- Stateful packet inspection
- User-aware policy enforcement
- SIP/H.323 NAT traversal
- ALG support for customized ports
- Protocol anomaly detection and protection
- Traffic anomaly detection and protection
- Flooding detection and protection
- DoS/DDoS protection
- RPS-enabled for desirable performance in chaotic environments

IPv6 Support

- Dual stack
- IPv4 tunneling (6rd and 6to4 transition tunnel)
- IPv6 addressing
- DNS
- DHCPv6
- Bridge
- VLAN
- PPPoE
- Static routing
- Policy routing
- Session control
- Firewall and ADP
- IPSec VPN
- Intrusion Detection and Prevention (IDP)
- Application Patrol
- Content Filtering 2.0
- Anti-Virus, Anti-Malware
- Anti-Spam

IPSec VPN

- Authentication: SHA-2 (512-bit), SHA-1 and MD5
- Encryption: AES (256-bit), 3DES and DES
- Support Route-based VPN Tunnel Interface (VTI)
- Key management: manual key, IKEv1 and IKEv2 with EAP
- Perfect forward secrecy (DH groups) support 1, 2, 5, 14
- IPSec NAT traversal
- Dead peer detection and relay detection
- PKI (X.509) certificate support

- VPN concentrator
- Simple wizard support
- VPN auto-reconnection
- VPN High Availability (HA): load-balancing and failover
- L2TP over IPSec
- GRE and GRE over IPSec
- NAT over IPSec
- Zyxel VPN client provisioning
- Support iOS L2TP/IKE/IKEv2 VPN Client provision

SSL VPN

- Supports Windows and Mac OS X
- Supports full tunnel mode
- HTTP, FTP, SMTP, POP3 and IMAP4 protocol support
- Automatic signature updates
- No file size limitation
- Supports 2-step authentication
- Customizable user portal

Intrusion Detection and Prevention (IDP)

- Routing and transparent (bridge) mode
- Signature-based and behavior-based scanning
- Automatic signature updates
- Customizable protection profile
- Customized signatures supported

Application Patrol

- Granular control over the most important applications
- Identifies and controls application behavior
- Supports over 15 application categories
- Application bandwidth management
- Supports user authentication
- Real-time statistics and reports
- SSL (HTTPS) inspection support
- IDP/ADP support on social networks such as likes and posts on Facebook

Anti-Virus

- Supports Anti-Virus signatures
- Identifies and blocks over 650,000 viruses
- Stream-based Anti-Virus engine
- HTTP, FTP, SMTP, POP3 and IMAP4 protocol support
- Automatic signature updates
- No file size limitation

Anti-Spam

- Transparent mail interception via SMTP and POP3 protocols
- Configurable POP3 and SMTP ports
- Sender-based IP reputation filter
- Recurrent Pattern Detection (RPD) technology
- Zero-hour virus outbreak protection
- X-Header support
- Blacklist and whitelist support
- Supports DNSBL checking
- Spam tag support
- Statistics report

Content Filtering 2.0

- Social media filtering
- Malicious Website filtering
- URL blocking and keyword blocking
- Blacklist and whitelist support
- Blocks java applets, cookies and ActiveX
- Dynamic, cloud-based URL filtering database
- Unlimited user license support
- Customizable warning messages and redirection URL
- HTTPs Domain filtering
- GeolP Blocking
- Monitors traffics based on country policy
- URL blocking and keyword blocking
- Supports to SafeSearch (SSL inspection must be enabled for this function)

SSL Inspection

- Certificate Trust Chain validation
- Support both inbound and outbound inspection
- Support Anti-virus / Content Filtering 2.0 / Application Patrol / IDP inspection
- Support TLS 1.0/1.1/1.2
- Visible bypass list

Unified Security Policy

- Unified policy management interface
- Supported UTM features: Anti-Virus, Anti-Spam, IDP, Content Filtering 2.0, Application Patrol, firewall (ACL)
- 3-tier configuration: object-based, profile-based, policy-based
- Policy criteria: zone, source and destination IP address, user, time
- Pre-defined UTM profiles for different user groups

WLAN Management

- Support [AP Controller version 3.0](#)
- Supports auto AP FW update
- Wireless L2 isolation
- Scheduled WiFi service
- Dynamic Channel Selection (DCS)
- Client steering for 5GHz priority and sticky client prevention
- Auto healing provides a stable and reliable coverage
- IEEE 802.1x authentication
- Captive portal Web authentication
- Customizable captive portal page
- RADIUS authentication
- WiFi Multimedia (WMM) wireless QoS
- CAPWAP discovery protocol
- Multiple SSID with VLAN
- Supports ZyMesh
- Support AP Forward Compatibility

Hotspot Management

- Integrated account generator, Web-based authentication portal and billing system
- Supports external RADIUS servers
- Per account bandwidth management
- User agreement login
- SP350E Service Gateway Printer enables one-click account and billing generation
- Built-in billing system
 - Time-to-finish accounting mode
 - Accumulation accounting mode
- Supports PayPal online payment
- Marketing tool
 - Advertisement link
 - Walled garden
 - Portal page
- Billing Replenish

Mobile Broadband

- WAN connection failover via 3G and 4G* USB modems
- Auto fallback when primary WAN recover

* For specific models supporting the 3G and 4G dongles on the list, please refer to the Zyxel product page at 3G dongle document.

Networking

- Routing mode, bridge mode and hybrid mode
- Ethernet and PPPoE
- NAT and PAT
- VLAN tagging (802.1Q)
- Virtual interface (alias interface)
- Policy-based routing (user-aware)
- Policy-based NAT (SNAT)
- Dynamic routing (RIPv1/v2 and OSPF)
- DHCP client/server/relay
- Dynamic DNS support
- WAN trunk for more than 2 ports
- Per host session limit
- Guaranteed bandwidth
- Maximum bandwidth
- Priority-bandwidth utilization
- Bandwidth limit per user
- Bandwidth limit per IP
- GRE
- BGP

Zyxel One Network

- ZON Utility
 - IP configuration
 - Web GUI access
 - Firmware upgrade
 - Password configuration
- Smart Connect
 - Location and system name update
 - Discover neighboring devices
 - One-click remote management access to the neighboring Zyxel devices

Authentication

- Local user database
- Microsoft Windows Active Directory integration
- External LDAP/RADIUS user database
- XAUTH, IKEv2 with EAP VPN authentication
- Web-based authentication
- Forced user authentication (transparent authentication)
- IP-MAC address binding
- SSO (Single Sign-On) support

Device High Availability Pro (HA Pro)

- Device failure detection and notification
- Supports ICMP and TCP ping check
- Link monitoring
- Configuration auto-sync
- Dedicated Heartbeat Link
- Smart handover
- NAT/Firewall/VPN Sessions synchronization

System Management

- Role-based administration
- Multiple administrator logins
- Supports Cloud Helper
- Multi-lingual Web GUI (HTTPS and HTTP)
- Command line interface (console, Web console, SSH and telnet)
- Cloud CNM SecuManager
- SNMP v1, v2c, v3
- System configuration rollback
- Firmware upgrade via FTP, FTP-TLS and Web GUI
- Dual firmware images

Logging and Monitoring

- Comprehensive local logging
- Syslog (to up to 4 servers)
- Email alerts (to up to 2 servers)
- Real-time traffic monitoring
- Built-in daily report
- Advanced reporting with Vantage Report

Services

Security

Product	Anti-Virus	Application Patrol & IDP	Content Filtering 2.0	Anti-Spam
USG110	1 year/2 years	1 year/2 years	1 year/2 years	1 year/2 years
USG210	1 year/2 years	1 year/2 years	1 year/2 years	1 year/2 years
USG310	1 year/2 years	1 year/2 years	1 year/2 years	1 year/2 years

Notes:

1. Zyxel USGs can be purchased with bundled 12-month standard license (Anti-Virus, Anti-Spam, Content Filtering 2.0 and IDP) with extra 1-month trial.
2. Licenses can be easily activated, renewed and managed at myZyxel
3. License bundles may vary according to region. Please contact your local sales representative for more information.

Connectivity & Industrial Solution

Product	SSL VPN Tunnels	SSL VPN Client ^{*1}	IPSec VPN Client
USG110	Add 5/10/50 Tunnels	For 1/5/10 client(s)	For 1/5/10/50 client(s)
USG210	Add 5/10/50 Tunnels	For 1/5/10 client(s)	For 1/5/10/50 client(s)
USG310	Add 5/10/50 Tunnels	For 1/5/10 client(s)	For 1/5/10/50 client(s)

*1: Support OS: MAC OS 10.7 or later

Product	Concurrent Device Upgrade ^{*1}	Hotspot Management ^{*2}	Managed APs	Device HA Pro ^{*1}	Vantage Report
USG110	100 nodes	1 year / One-time	Add 2/4/8 APs	One-time	For 1/5/25/100 device(s)
USG210	100 nodes	1 year / One-time	Add 2/4/8 APs	One-time	For 1/5/25/100 device(s)
USG310	100/300 nodes	1 year / One-time	Add 2/4/8 APs	One-time	For 1/5/25/100 device(s)

*1: With firmware ZLD 4.20 or later

*2: Hotspot Management supports for USG310 in firmware ZLD4.20 or later, and for USG110/210 in firmware ZLD4.25 or later.

Access Point Compatibility List

Product	Unified AP	Unified Pro AP
Models	<ul style="list-style-type: none"> • NWA5121-NI • NWA5121-N • NWA5123-NI • NWA5301-NJ 	<ul style="list-style-type: none"> • NWA5123-AC • WAC5302D-S • Forward Compatible APs*
		<ul style="list-style-type: none"> • WAC6502D-E • WAC6502D-S • WAC6503D-S
		<ul style="list-style-type: none"> • WAC6553D-E • WAC6103D-I • Forward Compatible APs*
Functions		
Central management	Yes	Yes
Auto provisioning	Yes	Yes
Data forwarding	Local bridge	Local bridge/Data tunnel
ZyMesh	Yes	Yes

*: From APC3.0, commercial gateways supporting APC technology are able to recognize APs with FW release higher than APC3.0 as Forward Compatible APs. Resellers can introduce newly-available Zyxel APs with basic features supported without upgrading any new controller firmware.

Accessories


SecuExtender Software

Item	Description	Supported OS
IPSec VPN Client*	IPSec VPN client software for the ZyWALL and USG Series with Easy VPN for zero-configuration remote access	<ul style="list-style-type: none"> • Windows XP (32-bit) • Windows Server 2003 (32-bit) • Windows Server 2008 (32/64-bit) • Windows Vista (32/64-bit) • Windows 7 (32/64-bit) • Windows 8 (32/64-bit) • Windows 10 (32/64-bit)
SSL VPN Client*	Secured VPN connection between PC/MAC and ZyWALL Firewall	<ul style="list-style-type: none"> • Windows XP • Windows 7 (32/64-bit) • Windows 8/8.1 (32/64-bit) • Windows 10 (32/64-bit) • MAC OS 10.7 or later

Notes:

*: A 30-day trial version of IPSec VPN client and SSL VPN client for MAC OS can be downloaded from official Zyxel website. To continue using the application, please contact your regional sales representatives and purchase a commercial license for the application.

Service Gateway Printer

Model	Feature	Supported Model
SP350E 	<ul style="list-style-type: none"> • Buttons: 3 • Paper roll width: 58 (+0/-1) mm • Interface: 10/100 Mbps RJ-45 port • Power input: 12V DC, 5A max. • Item dimensions (WxDxH): 176 x 111 x 114 mm (6.93" x 4.37" x 4.49") • Item weight: 0.8 kg (1.76 lb.) 	<ul style="list-style-type: none"> • VPN100 • VPN300 • USG110 • USG210 • USG310 • USG1100 • USG1900 • USG2200-VPN • ZyWALL 110 • ZyWALL 310 • ZyWALL 1100 • UAG2100 • UAG4100

Note: Hotspot management licenses required

ZYXEL

Your Networking Ally

For more product information, visit us on the web at www.zyxel.com

Copyright © 2018 Zyxel Communications Corp. All rights reserved. Zyxel, Zyxel logo are registered trademarks of Zyxel Communications Corp. All other brands, product names, or trademarks mentioned are the property of their respective owners. All specifications are subject to change without notice.

Datasheet [ZyWALL USG110/210/310](#)



5-100-00818010 04/18