



HR-S is an electro-mechanical room humidistat for controlling humidification and/or dehumidification in HVAC systems.

- * 1-step
- * Protection class IP30
- * Changeover contact 250 V AC, 5 A
- * High reliability and accuracy
- * Setpoint settings can be locked

Function

The humidistat uses a synthetic element as sensor medium. The synthetic element stretches as the humidity increases and shrinks as the humidity decreases. These changes are transmitted to a microswitch.

The setpoint knob affects the position of the microswitch in relation to the synthetic element. The setpoint can be set at between 35...95% RH.

Synthetic Element

We have developed a new synthetic element that gives a high accuracy at a low cost.

Setpoint knob can be locked

In order to eliminate the risk of tampering, the setpoint knob can be locked by means of a locking screw under the cover.

Typical applications

Can be used to control a humidifier or a dehumidifier or for on/off controlling of a fan. Can also be used to alarm when the humidity exceeds or falls below a pre-set level.

Technical data

General

Material casing	Polycarbonate
Ambient temperature	0...40°C
Mounting	Wall mounting
Protection class	IP30
CE	This Product confirms with the requirements of European LVD standards EN 60730-1:2000+A11+A12, EN 60730-2-13:1998+A1 and carries the CE-mark

Outputs

Changeover contact	250 V AC, 5 A
--------------------	---------------

Settings

Setpoint	35...95% RH
Hysteresis	+/- 4% RH


Wiring and Dimensions

Wiring

Humidification Closing contact between terminals 1 and 2

Dehumidification Closing contact between terminals 1 and 3

Dimensions



Head Office Sweden

Phone: +46 31 720 02 00
 Web: www.regin.se
 Mail: info@regin.se

Sales Offices

France:	+33 1 41 71 00 34	Hong Kong:	+852 24 07 02 81
Germany:	+49 30 77 99 40	Singapore:	+65 67 47 82 33
Spain:	+34 91 473 27 65		

THE CHALLENGER IN BUILDING AUTOMATION