

DURHAM MFG®

Est. 1922



Flammable Safety Cabinets



Part Number Manual Closing	Capacity Gallons (L)	Dimensions W x D x H - In (mm)	Shelves	Door Style	Ship Wt.
1012M-50	12 (45)	23" x 18" x 35" (584 x 457 x 889)	1	Manual	135 lbs.
1012S-50	12 (45)	23" x 18" x 36-3/8" (584 x 457 x 924)	1	Self Closing	155 lbs.
1030M-50	30 (114)	43" x 18" x 44" (1092 x 457 x 1118)	1	Manual	250 lbs.
1030S-50	30 (114)	43" x 18" x 45-3/8" (1092 x 457 x 1153)	1	Self Closing	270 lbs.
1045M-50	45 (170)	43" x 18" x 65" (1092 x 457 x 1651)	2	Manual	340 lbs.
1045S-50	45 (170)	43" x 18" x 66-3/8" (1092 x 457 x 1686)	2	Self Closing	360 lbs.
1060M-50	60 (227)	34" x 34" x 65" (864 x 864 x 1651)	2	Manual	379 lbs.
1060S-50	60 (227)	34" x 34" x 66-3/8" (864 x 864 x 1686)	2	Self Closing	399 lbs.
1090M-50	90 (340)	43" x 34" x 65" (1092 x 864 x 1651)	2	Manual	474 lbs.
1090S-50	90 (340)	43" x 34" x 66-3/8" (1092 x 864 x 1686)	2	Self Closing	505 lbs.

Flammable Safety Cabinet

- Sturdy all welded double wall steel construction
- 10 cabinets - 5 manual closing, 5 self closing
- 60 & 90 gallon models have internal 16 gauge reinforcements on bottom and sides
- 2" wide louvers support shelves, adjustable on 4" centers
- 2" Deep leak proof sump
- Safely contains hazardous chemicals, reducing the risk of fire
- Improved security with recessed lockable paddle latch and 3 point locking system
- 2" Bunged air vents with flame arrestors on each side of the cabinet allows for ventilation
- Safety yellow, High gloss, powder coat finish



Applications

Cabinets are required by OSHA and UFC in commercial and industrial facilities where flammable liquids are used and stored. Units conform to NFPA code 30 and OSHA 29 CFR 1910.106 and are FM approved.



www.durhammfg.com