



COREMAX H350

28 TO 30HRC
 DIN 8555 : MF-1-350P
 JIS Z3326 : YF2A-C-350

Diameter	Standard Package	Standard Pallet	List Price	Net Price
1.2mm	15kg Spool	1080kg		
1.6mm	15kg Spool	1080kg		

Applications

Hard surfacing of parts which is suitable for intermetallic abrasion and soil abrasion with light impact. Ideal for applications such as various wheels, shafts, gears, steel casting rollers and part of bulldozer, etc.

COREMAX H600

55 TO 58HRC
 DIN 8555 : MF-6-60-PT
 JIS Z3326 : YF3B-C-600

Diameter	Standard Package	Standard Pallet	List Price	Net Price
1.2mm	15kg Spool	1080kg		
1.6mm	15kg Spool	1080kg		

Applications

Hard surfacing of parts which is suitable for stronger intermetallic and soil abrasion with light impact. Ideal for applications such as various wheels bucket edges, sprockets and dipper teeth.

MAINTENANCE & REPAIR HARDFACING FLUX CORED WIRE

COREMAX H33

Chrome Carbide/60 TO 62HRC
 DIN 8555 : MF-10-60-CGT
 JIS Z3326 : YFCrA-C-700

Diameter	Standard Package	Standard Pallet	List Price	Net Price
1.6mm	15kg Spool/D270	1080kg		

Applications

High alloyed chromium carbide deposit for single layer welding very resistant to abrasion but very limited resistance to impact. The weld metal cracks to relieve cooling stresses. Ideal for application such as dredge pump component, wear plates, mixer blades, etc.