



## POWERWELD S-308L

AWS A5.9 : ER308L

Diameter	Standard Package	Standard Pallet	List Price	Net Price
2.4mm	25kg Coil	1000kg		
3.2mm	25kg Coil	1000kg		
4.0mm	25kg Coil	1000kg		



### Applications

It is an extra low carbon stainless wire used for common austenitic stainless steels referred to as "18% Cr- 8% Ni" steels. Typical for steels are 302, 304 and 304L.

## STAINLESS STEEL SAW WIRE

## POWERWELD S-309L

AWS A5.9 : ER309L

Diameter	Standard Package	Standard Pallet	List Price	Net Price
2.4mm	25kg Coil	1000kg		
3.2mm	25kg Coil	1000kg		
4.0mm	25kg Coil	1000kg		



### Applications

It is an extra low carbon stainless wire used for cladding and joining of dissimilar steels such as "18% Cr – 8% Ni" to mild steel. Also suitable for underlaying on ferritic steel for overlaying stainless steel weld metal.

## POWERWELD S-316L

AWS A5.9 : ER316L

Diameter	Standard Package	Standard Pallet	List Price	Net Price
2.4mm	25kg Coil	1000kg		
3.2mm	25kg Coil	1000kg		
4.0mm	25kg Coil	1000kg		



### Applications

It is an extra low carbon stainless wire used for joining and cladding of 316 and 316L stainless steel. Can be used on "18% Cr 8% Ni" steels.