

VERTICAL TYPE FLUX OVEN designed for re-baking re-conditioning and holding of submerged arc flux for high quality weld and assist you in protecting your welding profits.

SPECIFICATION

- Drive off Moisture & Get Better Weld.
- Secure, Moisture-Proof Storage.
- **STAINLESS STEEL BODY** to Prevent Rust and Iron Contamination.
- Sloped Chamber for Gravity-Flow Dispensability.
- Adjustable Thermostatic Control with Pilot Light and Temperature Gauge for Temperature Setting and Reading.
- Insulated and Vented Hinged Top Cover for Loading Method.



MODEL	F 100S	F 200S	F 300S
Capacity (estimate)	100 Liter (70kgs)	200 Liter (160kgs)	300 Liter (240kgs)
Temperature Range (Average Stabilized)	50° C ~ 300° C (122° F ~ 572° F)	50° C ~ 300° C (122° F ~ 572° F)	50° C ~ 300° C (122° F ~ 572° F)
Input Voltage AC - 50/60Hz	240 V	240 or 440 V (Specify one)	410 ~ 440 V (Specify one)
Heating Element	Tubular Type 1800 W	Tubular Type 2700 W	Tubular Type 3600 W
External Dimension H x D x W	1180 x 515 x 515 mm (46" x 20" x 20")	1250 x 610 x 610 mm (49" x 24" x 24")	1250 x 710 x 710 mm (49" x 28" x 28")
Body Insulation (Ceramic Wool)	50mm / 2"	50mm / 2"	50mm / 2"
Weight	53 kgs / 117 lbs	69 kgs / 152 lbs	86 kgs / 189 lbs