

CUT 100NA/120NA

INDUSTRIAL, IGBT, HF

- COMPRESSOR INSIDE, WITH MMA FUNCTION.



Processes

- CUT
- MMA

Package Includes

- Inverter power source
- CUT torch, 10m
- Earth clamp, 3m

Optional Accessories

- Electrode holder, 3m
- Air filter
- Hose, 3m



Features

- Compressor inside.
- CUT and MMA dual function.
- Quality cut up to 20/30mm thickness carbon steel, max cut up to 35/40mm carbon steel.
- Non-stop welding for 3.2 and 4.0mm electrode.
- 2T/4T, gas purge and gas source function select-able.
- Post-flow adjustable.
- Easy arc ignition with HF for cutting.
- Smooth and neat cutting surface.
- Tri-proof air duct design.

Model	Input Voltage/Phase/Frequency	Output Current/Voltage/Duty Cycle (40°C)	Amps Input At Rated Output	Output Range/ OCV	Dimension (mm)	Weight (kg)
CUT 100NA	380V/3P/50-60Hz	CUT:100A/120V/40% 70A/108V/100% MMA:280A/31.2V/40% 180A/27.2V/100%	CUT:23A@100A MMA:17.3A@280A	CUT:25-100A/270V MMA:100A-280A/67V	670*320*640	55.5
CUT 120NA	380V/3P/50-60Hz	CUT:110A/124V/40% 75A/110V/100% MMA:300A/32V/40% 200A/28V/100%	CUT:25.3A@110A MMA:18.5A@300A	CUT:25-110A/270V MMA:100A-300A/67V	670*320*640	55.5