

# Wall-Mounted Deluxe - R410A



## Features



### Energy Saving

Save more with the advance compressor and coil technology.



### Rapid Cooling

Achieve faster cooling with our true 5-speed fan design.



### Healthy Ionizer

Breathe fresher and healthier air for your family with the ion purifier.



### Quiet Mode

Experience peace and comfort at home with the use of the quiet mode.



### Air Surround

Feel the breeze with our 3D airflow technology that ensures even air circulation in your home.



### Elegant Design

Aesthetically designed with hidden temperature display on a classy high gloss surface.



## Other Features



Comfortable Sleep




Auto Mode



24 Hour Timer



Intelligent Air




Auto Swing



Exquisite Filter



3 Minutes Protection



Auto Restart



Self-Diagnosis

# Specifications

## Indoor Unit



## Outdoor Unit



## Wireless Remote Controller



## Wired Remote Controller (Optional)



Indoor Unit	Wireless	YWM3F10CAS-W	YWM3F15CAS-W	YWM3F20CBS-W
Outdoor Unit		YSL3F10AAS	YSL3F15AAS	YSL3F20AAS
Cooling Capacity	Btu/hr	10,000	13,000	18,600
Input Power	W	899	1,170	1,895
Rated Current	A	3.91	5.09	8.24
EER	Btu/hr/W	11.12	11.11	9.82
Power Source	Ph/V/Hz	1Ph/220-240V/50Hz		
Refrigerant Type/ Control		R410A / OUTDOOR CAP.TUBE		
Indoor Air Flow (H/L)	CFM	325/200	445/275	585/400
Noise Level (H/L)	dB(A)	33/28	40/34	42/35
Dimension (WxHxD)	Indoor	mm	815x280x205	855x280x204
	Outdoor	mm	780x540x245	780x540x245
Unit Weight	Indoor	kg	10.50	11.50
	Outdoor	kg	27.50	29.50
Refrigerant Piping	Liquid	mm/in	6.35 / 1/4	6.35 / 1/4
	Gas	mm/in	9.52 / 3/8	9.52 / 3/8

Indoor Unit	Wireless	YWM3F22CAS-W	YWM3F25CAS-W	YWM3F30CAS-W
Outdoor Unit		YSL3F22AAS	YSL3F25AAS	YSL3F30AAS
Cooling Capacity	Btu/hr	19,600	24,000	28,000
Input Power	W	2,000	2,450	2,855
Rated Current	A	8.70	10.65	12.41
EER	Btu/hr/W	9.80	9.80	9.81
Power Source	Ph/V/Hz	1Ph/220-240V/50Hz		
Refrigerant Type/ Control		R410A / OUTDOOR CAP.TUBE		
Indoor Air Flow (H/L)	CFM	650/400	710/465	710/465
Noise Level (H/L)	dB(A)	41/35	43/38	44/39
Dimension (WxHxD)	Indoor	mm	997x332x235	1,115x336x248
	Outdoor	mm	810x688x288	810x688x288
Unit Weight	Indoor	kg	12.00	16.30
	Outdoor	kg	44.00	47.00
Refrigerant Piping	Liquid	mm/in	6.35 / 1/4	9.52 / 3/8
	Gas	mm/in	12.70 / 1/2	15.88 / 5/8

Note:

- All designs and specifications are subjected to change without prior notice for product improvement
- Nominal cooling capacity is based on the conditions below  
Power supply, 1Ph/230V/50Hz  
Cooling - Indoor: 27°C DB /19°C WB and Outdoor 35°C DB / 24°C WB
- Units are tested and comply with the latest ISO5151

Head Office:

YORK (MALAYSIA) SALES & SERVICE SDN BHD (168496-T)  
Luxor Tech. Centre  
Level 2, No. 1A, Jalan Teknologi 3/4,  
Taman Sains Selangor 1, Kota Damansara PJU 5,  
47810, Petaling Jaya, Selangor Darul Ehsan.  
Tel: 03-7628 4100 Fax: 03-7628 4101

Branches:

Penang Branch  
Tel. 04-397 0213 Fax: 04-397 2045

Johor Bahru Branch  
Tel. 07-354 9878 Fax: 07-354 9871

Kota Kinabalu Branch  
Tel. 088-448 350 Fax: 088-448 352

Kuching Branch  
Tel. 082-553 100 Fax: 082-553 200

Customer Care Centre: 1800 - 88 - YORK (9675)  
Website: [www.york.com/my](http://www.york.com/my)



(Applicable to 2.8 HP and below)

Authorized Dealer