

Cassette Premium Inverter - R410A



(Applicable to 10,500~18,500 Btu/hr)



(Applicable to 26,500~50,000 Btu/hr)

Wireless Remote Controller



Wired Remote Controller (Optional)



Features



Inverter Technology

Experience a comfortable environment while enjoying higher saving with Inverter Technology.



Personalized Air Control

Four flaps personalized air control for individual air comfort.



4-Speed Drive

4-Speed Drive provides extra cooling during the hotter days.



Vertical Flow

Vertical Flow provides strong optimal airflow from heights up to 4.2 meters.



Air Surround

(Applicable to 26,500~50,000 Btu/hr)
Feel the air all around with the round air feature.



Other Features



Comfortable Sleep




Auto Mode



24 Hour Timer



High Performance Compressor



Water Pump



Fresh Air



3 Minutes Protection



Auto Restart



Self-Diagnosis

Specifications

Indoor Unit	Wireless	YCK5J10AAS-W	YCK5J15AAS-W	YCK5J20AAS-W	YCK5J25AAS-W
Outdoor Unit		YSM5J10AAS	YSM5J15AAS	YSM5J20AAS	YSM5J25AAS
Cooling Capacity	Btu/hr	10,500 (1,753~13,421)	13,200 (3,072~15,358)	18,500 (6,143~19,794)	26,500 (6,826~27,302)
Input Power	W	840 (280~1,800)	1,030 (280~1,800)	1,480 (550~2,000)	1,900 (400~3,200)
Rated Current	A	5.11 (1.2~8)	5.11 (1.2~8)	6.83 (2.3~9.5)	8.4 (2~15)
EER	Btu/hr/W	12.50	12.82	12.50	13.95
Power Source	Ph/V/Hz	1Ph/220-240V/50Hz			
Refrigerant Type/ Control		R410A / OUTDOOR ELECTRONIC EXPANSION VALVE			
Indoor Air Flow (H/L)	CFM	365/265	365/265	410/295	630/400
Noise Level (H/L)	dB(A)	40/32	40/32	42/35	36/29
Indoor Unit	Body Dimension(WxDxH)	mm	570x570x260	570x570x260	840x840x246
	Panel Dimension(WxDxH)	mm	700x700x60	700x700x60	950x950x50
	Net Weight Body	kg	18.5	18.5	31
	Net Weight Panel	kg	2.8	2.8	6.5
Outdoor Unit	Dimension (WxDxH)	mm	780x245x540	780x245x540	810x288x688
	Net Weight	kg	31.2	31.2	43
Refrigerant Piping	Liquid	mm/in	6.35 / 1/4	6.35 / 1/4	6.35 / 1/4
	Gas	mm/in	9.52 / 3/8	9.52 / 3/8	12.7 / 1/2

Indoor Unit	Wireless	YCK5J30AAS-W	YCK5J40AAS-W	YCK5J50AAS-W
Outdoor Unit		YSM5J30AAS	YSM5J40AAS	YSM5J50AAS
Cooling Capacity	Btu/hr	33,500 (8,532~34,128)	45,000 (11,945~49,486)	50,000 (11,945~52,898)
Input Power	W	2,550 (500~3,500)	3,600 (600~7,200)	3,900 (600~7,200)
Rated Current	A	11.7 (2.3~16)	6.3 (2.0~11.0)	7.00 (2.0~11.0)
EER	Btu/hr/W	13.14	12.50	12.82
Power Source	Ph/V/Hz	1Ph/220-240V/50Hz	3Ph/380-415V/50Hz	
Refrigerant Type/ Control		R410A / OUTDOOR ELECTRONIC EXPANSION VALVE		
Indoor Air Flow (H/L)	CFM	740/555	1,150/850	1,150/850
Noise Level (H/L)	dB(A)	41/33	47/38	47/38
Indoor Unit	Body Dimension(WxDxH)	mm	840x840x246	840x840x288
	Panel Dimension(WxDxH)	mm	950x950x50	950x950x50
	Net Weight Body	kg	31	32
	Net Weight Panel	kg	6.5	6.5
Outdoor Unit	Dimension (WxDxH)	mm	950x370x965	950x370x1,350
	Net Weight	kg	80	108
Refrigerant Piping	Liquid	mm/in	9.52 / 3/8	9.52 / 3/8
	Gas	mm/in	15.88 / 5/8	15.88 / 5/8

- Note:
- All designs and specifications are subjected to change without prior notice for product improvement
 - Nominal cooling capacity is based on the conditions below
Power supply, 1Ph/230V/50Hz or 3Ph/380V/50Hz
Cooling - Indoor: 27°C DB /19°C WB and Outdoor: 35°C DB / 24°C WB
 - Units are tested and comply with the latest ISO5151



(Applicable to 2.8 HP and below)

Head Office:

YORK (MALAYSIA) SALES & SERVICE SDN BHD (168496-T)
Bangunan THK, Suite 2.1, 2nd Floor,
No.2A, Jalan 243, Section 51A,
46100 Petaling Jaya, Selangor Darul Ehsan, Malaysia
Tel. 03-7628 4100 Fax: 03-7628 4101

Branches:

Penang Branch
Tel. 04-397 0213 Fax: 04-397 2045

Johor Bahru Branch
Tel. 07-354 9878 Fax: 07-354 9871

Kota Kinabalu Branch
Tel. 088-448 350 Fax: 088-448 352

Kuching Branch
Tel. 082-553 100 Fax: 082-553 200

Customer Care Centre: 1800 - 88 - YORK (9675)

Website: www.york.com/my



Authorized Dealer

YORK-MY-YCKI41-16-01