

Hisense

50 YEARS
ANNIVERSARY

Formidable Freezing Technology Leading



Global Freezing Solution Provider

International green technology advocate



R600a Environment Friendly

R600a is recognized as high purity isobutene, with low environmental impact, excellent thermodynamic performance, zero ODP and very low GWP (Global Warming Potential).



Metal Liner

Metal liner inner is solid, durable and it's easy to clean.



Over-temperature Alarm

Useful reminder you to protect food, the red indicator light when temperature rises unexpectedly up to -9°C in the freezer as a result of power cut off.



Wide-Range Climate Threshold

Freezer can operate normally in high temperature (43 °C) and low temperature (10 °C) environment.



Fast Freeze

The freezer will rapidly reach the desired temperature in the freezer by activating Fast Freeze function. It is particularly useful when freezing large quantity of food.



Adjustable Thermostat

Front mounted control knob to easily adjust freezer to desired temperature.



Water Disposal Device

Easy to defrost with Water Disposal Device.



Cut Off Power

When the temperature control knob rotate to the "off", the Freezer stopped cooling without having to unplug the power.



FC130D4BW

FC189D4BW

FC403D4BW

FC663D4BWB

FC533D4BWB

FC267D4BW

Model Name		FC130D4BW	FC189D4BW	FC267D4BW	FC403D4BW	FC533D4BWB	FC663D4BWB
Capacity	Net(L)	100	145	205	310	410	510
Performance							
Climatic type	(SN/N/ST/T)	T	T	T	T	T	T
Freezer Star rating	MS ISO 7371	4	4	4	4	4	4
Freezing capacity	kg/24h	7	9	12	17	20	23
Temperature range	°C	tf≤-18°C	tf≤-18°C	tf≤-18°C	tf≤-18°C	tf≤-18°C	tf≤-18°C
Max noise level	dB(A)	42	42	42	42	52	52
Power	V/Hz	220~240/50	220~240/50	220~240/50	220~240/50	220~240/50	220~240/50

Features							
	Refrigerant	R600a	R600a	R600a	R600a	R600a	R600
	Handle	Recessed	Grip F				
General Features	Temp .control	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical
	Panel	White	White	White	White	White	White
	Basket	1	1	1	2	2	2

Dimensions							
Net (With handle)	Width/mm	558	727	947	1125	1141	1702
	Depth /mm	485	560	560	709	709	709
	Height/mm	837	823	823	842	842	842
Net Weight	Kg	24	30	37	48	56	70



Hisense (Malaysia) Sdn Bhd

A-7-09, Capital 1, Oasis Square, 2, Jalan PJU 1A/7A, Oasis Damansara, 47301 Petaling Jaya, Selangor, Malaysia.

P: 03-7859-9550

F: 03-7859-8550

Careline: 1 300 888 550

Website: www.hisense.com.my

Facebook: www.facebook.com/HisenseMalaysia