

# BT-330

## INSTANT FLASHING TAPE



ISO 9001

**DESCRIPTION:**

**x'traseal®** BT-330 INSTANT FLASHING TAPE IS A BLACK, VERSATILE, SELF-ADHESIVE TAPE, COMPRISING AN ELSTOPLASTIC WEATHERPROOF BITUMEN COMPOUND COVERED BY A REINFORCES ALUMINIUM FILM. BITUMINOUS COMPOUND IS PROTECTED BY A SILICONIZED RELEASE FILM.

**FEATURES:**

- ◆ EASY TO APPLY
- ◆ WEATHERPROOF
- ◆ OUTSTANDING DURABILITY
- ◆ COST SAVING

**USES:**

- ◆ PROTECTION:  
ASPHALT, BRICKWORK, CONCRETE, FIBER CEMENT SHEETS, METAL AND PLASTIC MATERIALS ON ROOFS AND COVERING IN GENERAL.
- ◆ SEALING & WATERPROOFING:  
GLASS & PLASTIC WINDOW FRAMES, PARAPETS, SKYLIGHTS STRUCTURES, ETC.
- ◆ REPAIR WORK:  
METAL AND FIBER CEMENT SHEETS ROOFING, SHINGLES, GUTTERS AND METAL TUBE.

**WE RECOMMEND PRELIMINARY COMPATIBILITY TESTS PRIOR TO APPLICATION TO ACHIEVE DESIRABLE RESULTS**

**APPLICATION:**

- ◆ SURFACES MUST BE CLEAN, DUST-FREE AND DRY. RUST SHOULD BE REMOVED.
- ◆ CRACKS WIDER THAN 3MM SHOULD BE FILLED.
- ◆ REMOVE INSTANT FLASHING TAPE FROM THE RELEASE PAPER AND PRESS IT INTO POSITION USING FINGERTIP PRESSURE.
- ◆ USE A SEAM ROLLER TO SMOOTH OVER INSTANT FLASHING TAPE TO ENSURE GOOD CONTACT IS MADE.

**PHYSICAL PROPERTIES:**

SURFACE	PE COATED ALUMINIUM
ADHESIVE	BITUMINOUS COMPOUND
LINER	SILICONIZED FILM
THICKNESS	1.33MM (0.052IN)
TOTAL THICKNESS	1.50MM (0.059IN)

**WIDTH & LENGTH OF ROLL:**

<b>ROLL WIDTH</b>	<b>ROLL LENGTH</b>
50MM	10 METERS (11 YARDS)
75MM	10 METERS (11 YARDS)
100MM	10 METERS (11 YARDS)

**SPECIFICATION:**

TENSILE STRENGTH	65 N/MM <sup>2</sup>
TEAR STRENGTH	18 N/MM <sup>2</sup>
ELONGATION	11 % APPROX.
SOFTENING POINT	+ 95°C
COLD FLEXIBILITY	> -40°C
ADHESION ON STEEL	5.8 N/MM <sup>2</sup>
UV RESISTANCE	GOOD
SERVICE TEMPERATURE	-40°C TO 80°C
SHELF LIFE	12 MONTHS

**STORAGE:**

MATERIAL SHOULD BE STORED IN A DRY AND COOL PLACE BETWEEN +5°C TO +30°C.

**NOTE:**

DO NOT APPLY INSTANT FLASHING TAPE IF SURFACE TEMPERATURE IS BELOW 5°C.  
INSTANT FLASHING TAPE WILL BECOME BRITTLE IF ENCASED IN A CEMENTITIOUS MIX.  
INSTANT FLASHING TAPE IS NOT RESISTANT TO ACID AND ALKALINE.

**CAUTION:**

READ AND UNDERSTAND MATERIAL SAFETY DATA SHEET OF THIS PRODUCT BEFORE HANDLING OR USING.

*This information is provided in good faith and is believed accurate based on a review of current composition and information supplied by vendors. No warranty is expressed or implied. Liability is expressly disclaimed.*

