

MFY-01 Leak Tester is professionally designed for leakage test of packages for food, drugs, medical instruments, daily chemical products, cars, electronic components, stationeries and other industrial products. The instrument also can be used to test seal performance of specimens after falling and compression tests.



## Professional Technology

- The instrument utilizes the digital preset design of vacuum degree and vacuum retention time to ensure the accuracy of test data
- Top quality parts and components made by world famous brands are used to ensure reliable overall product performance
- Specimens could be tested in the preset vacuum condition by automatic compensation of constant pressure
- Professional software supports automatic back flushing and test termination to provide a safe test environment
- The instrument is controlled by micro-computer, with LCD and PVC operation panel, which is convenient for customers to test and view test data

## Test Principle

Firstly submerge the specimen in the water within the vacuum chamber, and then evacuate the vacuum chamber to form differential pressure between the inside and outside of specimen. The leakage property could be obtained by observing the steady progression of bubbles from the specimen and how the specimen expands and restores to its original shape after vacuum release.

This test instrument conforms to the standards: GB/T 15171, ASTM D3078

## Applications

MFY-01 leak tester is applicable to the determination of leakage property of:

<b>Basic Applications</b>	Glass Bottles, Pipes, Cans and Boxes
	Plastic Bottles, Pipes, Cans and Boxes
	Metal Bottles, Pipes, Cans and Boxes
	Paper Plastic Composite Bags and Boxes
<b>Extended Applications</b>	Pen Refills
	Electronic Components
	Medical Instruments

## Technical Specifications

<b>Specifications</b>	<b>MFY-01</b>
<b>Vacuum Degree</b>	0 ~ - 90KPa
<b>Accuracy</b>	1% FS
<b>Vacuum Chamber</b>	Φ270 mm x 210 mm (H) (standard)
	Φ360 mm x 585 mm (H) (optional)
	Φ460 mm x 330 mm (H) (optional)
<b>Effective Sizes</b>	Note: customization is available for other sizes
<b>Gas Supply Pressure</b>	0.7 MPa (outside of supply scope)
<b>Port Size</b>	Φ6 mm PU Tubing
<b>Instrument Dimension</b>	300 mm (L) x 380 mm (W) x 450 mm (H)
<b>Power Supply</b>	220VAC 50Hz / 120VAC 60Hz
<b>Net Weight</b>	12 kg

Note: 1. The gas supply port of the instrument is Φ6 mm PU tubing;

2. Customers will need to prepare for gas supply.