HVAC/R Service Products

TAP



Wireless Temperature And Pressure Gauge Set



6285 Hitzkirch - Switzerland

Tel.: +41 41 919 72 82 Fax: +41 41 919 72 83


info@refco.ch www.refco.ch

TAP

The new wireless digital pressure and temperature gauge set TAP is a user friendly measuring instrument to measure temperature and pressure from the low and high sides of air conditioning and refrigeration systems.

- Quick and easy connection to pressure source and temperature measuring point.
- The wireless K-type temperature clamp, equipped with digital display, is applicable for pipe diameters from 6 mm to 42 mm (1/4" to 1 5/8").
- Measurements and calculation of superheat or subcooling can be shown on pressure gauge display and / or on your mobile device.
- Up to 6 TAP devices can be monitored on your mobile device.
- Create report on mobile phone and send by e-mail to your office.
- Use of common AAA batteries.
- TAP is delivered in a handy case either as single or double set.





Online

FRATOR

P2 11.2

TOVE 15

T2

AT

On/Off button

Select botton

- On/Off button

- Display



Offline

Display

Select buttor

Menu button



Features and Benefits



Display on temperature clamp

Wireless no cable needed

No smart device needed

IOS compatible

Android compatible

2

(I)

Synchronized with App

Calculate superheat and subcooling

Reports stored on smart device and E-mailed

Library of over 50 refrigerants stored

> Connect up to 6 pressure gauges and temperature clamps

Pressure Gauge and Temperature Clamp standalone

Refrigerant updates available via Micro USB connection

Technical Specification

TAP Pressure Gauge

IAF FIESSUIE Gauge	
Refrigerant:	More than 50 refrigerant tables included
Pressure range:	Up to 60 bar (870 psi)
Accuracy:	≤1.0 % FS
Resolution:	0.07 bar / 0.1 psi
Units:	bar / psi / kPa / MPa
Max (Proof) overpressure:	60 bar (870 psi)
Backlit LCD display:	40 mm x 30 mm
Automatic power save mode:	Configurable: 10 min / 20 min / Off
Low battery indication:	When battery level is less 30%
Power:	Battery 4 x AAA
Battery life:	40 h
Interface:	Micro USB
Connection fitting:	1/4" SAE
Including adapters:	1/4" SAE female/female
Size:	125 mm x 57 mm x 34 mm
Weight:	~200 gr / 7 oz

TAP Temperature Clamp

Type:	К-Туре
Temperature range:	-40°C to +125°C
Accuracy:	± 1°C
Resolution:	0.1°C
Temperature units:	°C / °F
Backlit LCD display:	35 mm x 15 mm
Power:	Battery 3 x AAA
Battery life:	50 h
Jaw range:	6 mm to 42 mm (1/4" to 1 5/8")
Size:	160 mm x 40 mm x 80 mm
Weight:	~180 gr / 6 oz

App Requirements

iOS:	Version 8.0 or higher	
Android:	Version 4.4 or higher	
Get the App for iPhone, iPad on App Store™, for Android on Play Store		

Article Overview

Designation	Description	Part No.	
TAP-SET	• 1 TAP Pressure Gauge		
	• 1 TAP Temperature Clamp		
	• 1 SAE 1/4" female/female adapter		
	• 1 USB Cable	4687788	
	• 7 Batteries		
	• 1 Manual		
	• 1 Case		
TAP-DOUBLE-SET	• 2 TAP Pressure Gauges		
	• 2 TAP Temperature Clamps		
	• 2 SAE 1/4" female/female adapter		
	• 1 USB Cable	4687789	
	• 14 Batteries		
	• 1 Manual		
	• 1 Case		
TAP	Pressure Gauge	4687787	
TAP-CLAMP	• Temperature Clamp	4687785	

Further available accessories (optional)

CL-6-R	1/4" SAE Hose red, 15 cm, 6"	9881265
CL-6-B	1/4" SAE Hose blue, 15 cm, 6"	9881256
SWIVEL-ARM- 1/4"SAE-N	Swivel arm 1/4" SAE	4687631
A-31851/10	Threaded T style 1/4" SAE female with swivel nut x 1/4" SAE x 1/4" SAE, 10 pcs.	9884841
QC-S410A/2	Adapter with core depressor, 1/4" SAE x 1/2"-20UNF, 2 pcs	4687095
QC-S4A-1/4"SAE/2	Quick coupler straight 1/4" SAE x 1/4" SAE, 2 pcs.	4687823
QC-S4A-5/16"SAE/2	Quick coupler straight 1/4" SAE x 5/16" SAE, 2 pcs.	4687824
TAP-MARKING- RING-SET	Marking rings for TAP 4 x 5 pcs. per size	4687793