

TMI**LOW SMOKE ZERO HALOGEN PVC COATED
FLEXIBLE CONDUIT (BS EN 61386)****Square-lock, Galvanized Steel, LSZH Jacket (Black)****Temperature** : -30°C~+80°C**Range** : IP 40 (Fit with connector series: TMI 09)**IP Rating** : IP 65 (Fit with connector series: TMI 09)**Jacket Colour** : Black (Standard), other colors are available by consult.**Flexibility** : High**Fire Retardant** : Self-extinguishing**UV Resistance** : By ordering**Tensile Resistance** : Light: 250N / Medium: 500N / Heavy: 800N**RoHS Compliance** : Yes**Certificate** : SIRIM Test**Profile** :

PART NUMBER	ID (mm)	OD w/ Jacket (mm)	Bending Radius (mm)	Package/Roll (m)	Measurement (LxWxH mm)
TMI13LSZH-20	16.9	21.5	75	30	430*430*200
TMI13LSZH-25	21.4	26.0	75	30	500*500*150
TMI13LSZH-32	28.1	34.0	105	15	500*500*300
TMI13LSZH-40	37.7	44.5	125	15	500*500*320
TMI13LSZH-50	48.4	55.0	175	15	500*500*350

APPLICATIONS:

For use in connecting machinery in processing plants and areas subject to sparks, heat and environments where extreme hazards may cause damage to cables. The PVC Coating offers an IP65 rating when used in conjunction with our Galvanise Flexi-Conduit connectors.

CONSTRUCTION:

Galvanised metal conduit with a flame retardant, low smoke zero halogen PVC cover suitable for transit and transportation systems. Corrosion, abrasion, oil and water resistant. High flexibility.

PRODUCT FEATURES:

- High mechanical strength
- Superior oil, grease and weather resistant