

Suzuki Latex Industry Malaysia Sdn. Bhd.

(162802-K)





Lot 14, Jalan 26/1, Seksyen 26, Kawasan Perindustrian HICOM, 40000 Shah Alam, Selangor Darul Ehsan, Malaysia.

Tel: 603-51911540 Fax: 603-51911133 Website: http://www.suzukilatex.com.my

Product Specification.

MASK BLACK Thick Finger Stalls (Static Dissipative).

Chemical Description.

MASK BLACK finger stalls are manufactured from 100% pure natural rubber latex.

Specifications.

Specified Properties	Thick Type		
	A 20	B 18	C 15
Internal diameter (mm)	20	18	15.5
Thickness (mm)	0.41 (+0.05 / -0.02)	0.39 (+ 0.05 / - 0.02)	0.37 (+0.05 / -0.02)
Length (mm)	50 <u>+</u> 2	47 <u>+</u> 2	41 <u>+</u> 2
Physical Test (ASTM D412)			
Elongation	Min 700%		
Tensile Strength	Min 25 Mpa		
Average Surface Resistivity (ASTM D257)	$10^6 \sim 10^8$ Ohm/square		

Product range and packaging specifications.

Box packing

Products size	Packings	
A 20	10 pcs. X 10 packets x 50 boxes per carton	
B 18		
C 15		

Functions.

- This powder free finger stalls suitable to use in Cleanroom Class 1000.
- To protect fingers of workers.
- To prevent contamination caused by direct contact with fingers.
- Rough surface provides better grip and anti-slip properties.
- Powder free for use in clean room environment.
- Suitable for heavy duty use that requires ESD properties.

Applications.

- electronics industries
- mechantronics industries
- optotronics industries

Recommended Storage Conditions.

Store indoor at room temperature below 28°C.

Avoid direct exposure to sunlight.

Once open, use immediately.

Shelf life.

Approximately 9 months.

If finger stall contaminated, please dispose as Scheduled Wastes. Finger stall is bio-degradable type.

Document no SLM-WI-PRS-001 Revision 00 Page 1 of 1