

Suzuki Latex Industry Malaysia Sdn. Bhd.

(162802-K)





Lot 14, Jalan 26/1, Seksyen 26, Kawasan Perindustrian HICOM, 40000 Shah Alam, Selangor Darul Ehsan, Malaysia.

Tel: 603-51911540 Fax: 603-51911133 Website: http://www.suzukilatex.com.my

Product Specification.

SHIELD Finger Stalls.

Chemical Description.

SHIELD finger stalls are manufactured from 100% pure natural rubber latex.

Specifications.

S pecifications:		
Specified properties	1-A19	1-B15
Internal diameter (mm)	19	15
Thickness (mm)	0.34 ± 0.02	
Length (mm)	56 <u>+</u> 2	61 <u>+</u> 2
Physical Test (ASTM D412)		
Elongation	Min 700 %	
Tensile Strength	Min 25 Mpa	

Product range and nackaging specifications

1 roduct range and packaging specifications.		
Product Size	Packaging	
1-A19 1-B15	10 pcs. X 10 bags X 50 boxes per carton 300 pcs. X 30 bags per carton	

Functions.

- To protect fingers of workers.
- To prevent contamination caused by direct contact with fingers.
- Rough surface provides better grip and anti-slip properties.
- It is thick but soft, ideal for prolonged usage

Applications.

- mechanical industries
- mechantronics industries
- ideal for office work

Recommended Storage Conditions.

Store indoor at room temperature below 28°C.

Avoid direct exposure to sunlight.

Once open, use immediately.

Shelf life.

Approximately 12 months.

If finger stall contaminated, please dispose as Scheduled Wastes. Finger stall is bio-degradable type.

Document no PRS-QCO-430 Revision 00 Page 1 of 1

Date: 06 Feb'2017