



LUMINAIRE SPECIFICATIONS

▪ Voltage	AC 220~240V 50/60Hz
▪ Power	50W, 80W, 100W, 120W, 150W, 200W.
▪ Power Factor	0.95
▪ Ingress Protection	65
▪ Impact Protection	08
▪ Operation Temp	- 30 ~+55°C
▪ Beam Angle	80° x 120°
▪ Optical Cover	PC
▪ Fitting Material	Die Cast Aluminum Anti Corrosive Treatment
▪ Socket Diameter	∅ 60mm.
▪ Compliance	EN60598-1, EN60598-2-1 EN62031, EN62493, EN62471, EN55015, EN61547, EN61000-3-2 EN61000-3-3.

LED MODULE SPECIFICATIONS

▪ Color Temperature	3000K, 4000K & 5000K
▪ Luminous Efficiency	110LM/W
▪ Color Rendering Index	≥ 80
▪ Lifespan	50,000 hours (Ta=30 @L70)
▪ Compliance	LM 80

Driver SPECIFICATIONS

▪ Protection	Over Voltage Over Current Over Temperature Surge Immunity 10KV
▪ Compliance	EN55015, EN61000-3-2 EN61000-3-3 EN61000-4-2,3,4,5,6,8,11 EN61547

Product Certifications



LVD

EMC



Remarks:

Detail and specification are current at the time of publication but may be changed without prior notice

APPLICATION

- Factory Road Lighting, Parking Area, Residential Road, Access way, Express Road.



PRODUCT CODE

- MXP-SL050-RST-F 50W
- MXP-SL080-RST-F 80W
- MXP-SL100-RST-F 100W
- MXP-SL120-RST-F 120W
- MXP-SL150-RST-F 150W
- MXP-SL200-RST-F 200W


LUMINOUS FLUX

- 5,500 Lumen
- 8,800 Lumen
- 11,000 Lumen
- 13,200 Lumen
- 16,500 Lumen
- 22,000Lumen




Dimension & Weight

50W
2.2Kg




Ø62mm

150W
4.2Kg




Ø62mm

100W
3.5Kg



Ø62mm

200W
5.2Kg



Ø62mm