



BACKLIT LED Panel Light



Application



- Office, Hall, Mall, Warehouse, Hotel, Lab, Retail Shop and etc...

Product Description

- Power available from 40W & 72W.
- Recessed and Surface mounted optional available.
- High Brightness at >100 LM/W with LM 80 certified LED Chips.
- Combined with LED Lens provides uniform light distribution.
- Fitting frame is made by 6063 pure aluminum and full-automatic laser welding process, to avoid light leakage and out of the shape.


Electrical Protection

- ✓ Over output - Voltage Protection
- ✓ Over output - Current Protection
- ✓ Short Circuit Protection
- ✓ Over Temperature Protection
- ✓ Surge Protection 1KV



Model & Specification

Model	EGE-PNL22-P040	EGE-PNL14-P048	EGE-PNL24-P072
Input Voltage	AC 175 ~ 277V		
Frequency	50/60Hz		
Operating Current	0.20A	0.20A	0.30A
Power Rating	40W	40W	72W
Power Factor	> 0.9		
CRI	> 80 Ra		
Operating Temp	- 20° + 50°		
Luminous Flux	≥ 4000 Lm	≥ 4000 Lm	≥ 7200 Lm
Color	3000K / 4000K / 6500K		
THD	≤ 15%		
Length	595X595MM	295X1195MM	595X1195MM
Driver	Isolated Driver/Non-Flicker		
Lighting Source	SMD 2835		
Cover option	Frost		
Beam Angel	110°		
Material	Aluminum/PMMA		
Life span	> 25000Hrs		
Energy Saving	≥ 60%		
Certification	CE EMC, LVD, RoHS		
Qty / Carton	8pcs	4pcs	4pcs



595 X 595MM

295 X 1195MM



595 X 1195MM



Remarks:

Detail and specification are current at the time of publication but may be changed without prior notice

