



LED Tri Proof Lamp (TPL)



Application

- ☐ Suitable use in Indoor and Outdoor, Clean Room, Subway Station, Warehouse, Basement, Bus Station, Hypermarket, Workshop, Car Park, Tunnel

Product Description

- Power available from 20W, 40W, 50W & 60W.
- High Brightness at >130 LM/W Used of original Lumileds LED Chip with LM 80 certified.
- Superior thermal management ~ An even heat distribution for greater cooling capacity.
- The anodic oxidation treatment fitting with strong corrosion resistance.
- Aluminum cooling efficiency + PC lampshade high light transmittance.

Model	EGE-TPL020-LT06	EGE-TPL-040-LT12	EGE-TPL050-LT12	EGE-TPL060-LT15
Input Voltage	AC220V~240V			
Frequency	50/60 Hz			
Power Rating	20 ± 1W	40 ± 2W	50 ± 2W	60 ± 2W
Power Factor	≥ 0.95			
Output Current	0.085A	0.167A	0.208A	0.25A
Working Temp	-25° C + 45° C			
Total Harmonic Distortion	≤ 15%			
Luminous Efficiency	130 LM/W ± 5%			
Luminous Flux	2600LM	5200LM	6500LM	7500LM
Power Efficiency	> 95%			
CRI	Ra ≥ 80			
Color Temp	3000K/ 4000K/5000K/6000K			
Driver Source	Lifud			
LED Source	Lumileds			
Dimension	600*93*77	1200*93*77	1200*93*77	1500*93*77
IP Rating	IP 65			
Beam Angle	120°			
Material	Aluminum / PC			
Lifespan (LM80)	>50000Hrs(Ta=30°C@L70)			
Certification	CE, LVD, EMC, RoHS			