

SUNLUX™ LED HIGH BAY (XJN)

APPLICATION

- Factory and Manufacturing plant, Warehouse, Stadium, Hall, Mall, Exhibition Hall, Toll Counter and etc.



Power	Part Number	Luminous Flux
▪ 100W	SLX-HB100-XJN	13000 Lumen
▪ 150W	SLX-HB150-XJN	19500 Lumen
▪ 200W	SLX-HB200-XJN	26000 Lumen

LED MODULE SPECIFICATIONS

- Color Temperature 6000K
- Luminous Efficiency 130LM/W
- Color Rendering Index ≥ 70
- Lifespan 30,000 hours (Ta=30 @L70)
- Compliance LM 80
- **Protection** Over Voltage
Over Current
Over Temperature
Surge $\geq 4KV$

Fitting	Size(mm)	Weight
▪ 100W	$\varnothing 309.5 \times 52.7$	1.7KG
▪ 150W	$\varnothing 364.2 \times 55.7$	2.2KG
▪ 200W	$\varnothing 409.2 \times 57.7$	3.0KG

LUMINAIRE SPECIFICATIONS

- Voltage AC 100~277V 50/60Hz
- Power 100W, 150W, 200W.
- Power Factor 0.95
- Ingress Protection 65
- Impact Protection 08
- Operation Temp $-30 \sim +55^{\circ}C$
- Beam Angle 90° & 120° .
- Optical Cover Polycarbonate
- Fitting Material Die Cast Aluminum with Anti Corrosive Treatment
- Installation Method Hook, Bracket.
- Compliance EN60598-1, EN60598-2-1
EN62031, EN62493,
EN62471, EN55015,
EN61547, EN61000-3-2
EN61000-3-3.