

## APPLICATION

- Guard Post, Car Park, Walkway, Signboard, Playground, Garden and etc.



### Power

50W	SLX-FL050-ZXN	7000 ± 5% Lumen
100W	SLX-FL100-ZXN	14000 ± 5% Lumen
150W	SLX-FL150-ZXN	21000 ± 5% Lumen
200W	SLX-FL200-ZXN	28000 ± 5% Lumen
300W	SLX-FL300-ZXN	42000 ± 5% Lumen
400W	SLX-FL400-ZXN	56000 ± 5% Lumen

### Fitting

Fitting	Size(mm)	Weight
50W	198*188*35	0.9KG
100W	270*273*35	1.7KG
150W	333*313*35	2.7KG
200W	360*363*35	3.0KG
300W	460*348*38	5.1KG
400W	594*350*38	6.0KG

### Protection

Over Voltage  
Over Current  
Over Temperature  
Surge ≥ 4KV

### LED Module Specifications

- Color Temperature: 3000K & 6000K
- Luminous Efficiency: 140± 5% LM/W
- Color Rendering Index: ≥ 80
- Compliance: LM 80
- Lifespan: ≥ 30,000 hour

### Luminaire Specifications

- Voltage: AC 160~265V 50/60Hz
- Power: 50W, 100W, 150W, 200W, 300W, 400W.
- Power Factor: 0.60
- Ingress Protection: IP67
- Operation Temp: - 40°C to +50°C
- Beam Angles: 110°
- Optical Cover: Tempered Glass
- Fitting Material: Die Cast Aluminum with Anti Corrosive Treatment
- Installation Method: Bracket