



## LUMINAIRE SPECIFICATIONS

▪ Voltage	AC 220~240V 50/60Hz
▪ Power	50W, 100W, 150W, 200W
▪ Power Factor	0.95
▪ Ingress Protection	65
▪ Impact Protection	08
▪ Operation Temp	- 30 ~+50°C
▪ Beam Angle	140° X 75°
▪ Optical Cover	PC
▪ Fitting Material	Die Cast Aluminum Anti Corrosive Treatment
▪ Socket Diameter	∅ 40 / 60mm.
▪ Compliance	EN60598-1, EN60598-2-1 EN62031, EN62493, EN62471, EN55015, EN61547, EN61000-3-2 EN61000-3-3.

## LED MODULE SPECIFICATIONS

▪ Color Temperature	3000K, 4000K, 5000K.
▪ Luminous Efficiency	130LM/W±5%
▪ Color Rendering Index	≥ 70
▪ Lifespan	30,000 hours (Ta=30 @L70)
▪ Compliance	LM 70

## Driver SPECIFICATIONS

▪ Protection	Over Voltage Over Current Over Temperature Surge Immunity 4KV
▪ Compliance	EN55015, EN61000-3-2 EN61000-3-3 EN61000-4-2,3,4,5,6,8,11 EN61547

## APPLICATION

- Factory Road Lighting, Parking Area, Residential Road, Access way, Express Road.



## PRODUCT CODE

- SLX-SL050-DL33      50W
- SLX-SL100-DL33     100W
- SLX-SL150-DL33     150W
- SLX-SL200-DL33     200W

## LUMINOUS FLUX

- 6,500 Lumen
- 13,000 Lumen
- 19,500 Lumen
- 26,000Lumen



## Dimension & Weight

Power	Weight	Dimension	Arm Diameter
50W	2.6 Kg	375*150*65	Ø 40mm
100W	3.6 Kg	525*180*75	Ø 62mm
150W	5.3 Kg	650*260*95	
200W	6.2 Kg	700*200*95	