HUAHENG




Welding System

HUAHENG WELDING CO., LTD.

TOK series

Open Tube to Tube Welding Head



Brief Introduction

This welding head is special designed for tube to tube TIG welding, suitable for carbon steel, stainless steel tube to tube connection, mainly for wire feeding or self–fusion.

Support equipment: i—Arc200 and i—Arc400 Programmable Orbital Welding Power Source.

Application: chemical, food, medicine, engineering installation, boiler, military, nuclear and so on.

Technical Specification		
	TOK43	TOK77
Material	Carbon steel, stainless steel	Carbon steel, stainless steel
Tube OD (mm)	Outer clamp: $\Phi15 \sim \Phi25 (5/8" \sim 1")$ Inner clamp: $\Phi25 \sim \Phi43 (1" \sim 15/8")$	Outer clamp: Φ 19.05 ~ Φ 45 (3/4" ~ 1 3/4" Inner clamp: Φ 45 ~ Φ 77 (1 3/4" ~ 3")
Tungsten diameter (mm)	Φ2.4	Φ2.4
Rotation speed (rpm)	0.37~7.45	0.19 ~ 3.8
Protective gas	Ar	Ar
Cooling	Water	Water
Cooling flow (ml/min)	≥600	≥600
Dimension (mm)		
A	128	180
В	115	120
C	85 ~ 92	95 ~ 101
D	165	92
E	44	82
F	230	290
Weight (kg)	2.5 (no cable)	4.0 (no cable)
Dimension (mm)	305 × 128 × 230	310 × 180 × 290




Features

- Suitable for thin wall thickness carbon steel, stainless steel tube or pipe orbital welding;
- Suitable for connection of tube to tube, tube to flange, tube to elbow, tube to valve and so on;
- Automatic all position TIG tube to tube welding with/without wire feeding;
- Water circuit cooling, achieving long time working;
- Mechanical profile tracking design, ensure seam quality.





HUAHENG



Add: No.1588 Boshi Road, Kunshan, Jiangsu, P.R. China. PC: 215347 Tel: +86(0)512-81866666 Fax: +86(0)512-57328188 www.huahengweld.com E-mail: info@huahengweld.com