

## Portable Industrial LED Film Viewer

# FV-2010 Plus



Click this key  
to change window size

- ▶ **Electronic Light mask - World First**
- ▶ **Larger size: 400×100mm (15.8×4 inch)**
- ▶ **Low noise: Fan with temperature depended**
- ▶ **2 years free service guarantee**
- ▶ **CE Approved**

**MAX.L=130,000Cd/m**

**g=0.95**

**σ'=0.95**

### Characteristic:

- Luminance : 130,000Cd/m<sup>2</sup> (408,200Lux)
- Uniformity: 0.95 , Diffusion factor:0.95
- Window Size: 400×100mm (15.8×4")
- Weight less than 4.0 Kg (8.8lbs)
- 12 hours continues maximum luminance,  
Surface temperature rise ≤ 18℃
- Unlimited dimmer from 5%-100%
- Free 2 years service guarantee
- CE Approved

### What is electronic light mask?

Traditionally we use a series of metallic light masks which are mount on the surface of film viewers. It is inconvenient when you replace the light masks when you want to change the size of light, and energy waste because it just mask the light where you do not need, but the entire light screen is still turn on.

Electronic light mask is electronics controlled, the light screen is divided into 6 parts, you can turn on or turn off each parts of light screen by press one key. With the help of it, you just turn on the area you need, it will be convenient when you change the size of light, low heat and low energy cost.

The size of light will be switched as below:



### Spare parts list:

Description	Quantity
Power adaptor & Line	1
Foot pedal	1
Light mask (15.8 2.7")	1
Instruction (English)	1
Guarantee and report (English)	1

### Specification:

Max Luminance: ≥ 130,000Cd/M <sup>2</sup> (408,200Lux)	Uniformity: g=0.95
Diffusion Factor: σ'=0.95	Viewer window: 400×100mm (15.8×4 inch)
Surface temp. rise ≤ 18℃ After 12 hours continues maximum luminance	Power: 85-264VAC 47~63Hz. (Full range)
Dimension: 600 80 1 60mm 23.6 3.1 6.3 inch (L W H)	Weight: 4Kg (8.8 lbs)

### WenZhou LuCheng NDT Equipment Corp.

Manufacturer of NDT equipments  
RM.308,Kang Yuan South Building XinCheng Road,  
325000 WenZhou, P.R.China.

Tel.:0086-577-88293040  
Fax:0086-577-88259689  
Web:www.Lcndt.net  
E-mail:Lcndt@163.com

**LCNDT 鹿成**

www.Lcndt.net <sup>®</sup>



ISO9001 Registered

### PRODUCT CERTIFICATE

PRODUCT Industrial LED film viewer  
MODEL FV-2010 Plus  
SERIAL NO. 101060  
MEASUREMENT BASED ON EN 25580 / ISO5580 / ASTM E1390-90 / ASTM E1390-12  
MEASUREMENT RESULT QC Passed

#### Testing Report:

Maximum Luminance: 130,000Cd/M<sup>2</sup> Uniformity g: 0.95

Diffusion factor  $\sigma'$ : 0.95 Maximum Reading Density: 4.1 H/D

Film Density	ASTM/EN/ISO MIN. Cd/m <sup>2</sup>	TEST MAX. Cd/m <sup>2</sup>
2.21	30	726.70
2.72	10	213.20
3.66	10	24.70
4.29	10	7.60

NOTE: The luminance mentioned in above table is measured light through the film.



INSPECTOR INSPECTOR 3

MANAGER INSPECTOR 1

Date of Measurement: 2014.10.27

**Lu Cheng NDT Equipment Corp.**

E-mail: [Sales@Lcndt.net](mailto:Sales@Lcndt.net) (For sales) [gm@Lcndt.net](mailto:gm@Lcndt.net) (For service)

Http://www.Lcndt.net

Phone: 86-577-88293040 Fax: 86-577-88259689