



PCP 28 LCD 400V



DIGITAL
DISPLAY

Overview

PCP 28 LCD 400V

cod. 824053

Column spot welding machine with movable arms, microprocessor digitally controlled. The digital, multifunction LCD control panel allows to operate: in EASY mode (setting of spot welding current and time); in EXPERT mode (setting of different spot welding parameters) storing up to 20 customised programmes. It operates both in continuous and pulse mode and grants optimum results on different kinds of steel.

Features:

- adjustment of spot welding current (%), time (cycles), force and speed rate of electrodes compression
- choice of various parameters of the spot welding cycle (approach, slope, welding and pause time and pulse number)
- easy to read LCD display
- pneumatic pedal control
- gap setting of the arms
- thermal protection with indicator.
- air flow regulation for the slow closing of the arms

The model requires water cooling for electrodes and arms.

Technical data

CODE 824053	RATED POWER X=50% 25 k VA	PROTECTION DEGREE IP20
DOUBLE PHASE MAINS VOLTAGE 400 V	POWER FACTOR (cosphi) 0,7	DIMENSIONS 79 - 32 - 128 cm
MAINS FREQUENCY 50 / 60 Hz	MAX WELD.THICK. ON 2 SHEETS 5 + 5 mm	WEIGHT 148 kg
MAX SPOT-WELDING CURRENT 16400 A	MAX ELECTRODES POWER 220 daN	EAN CODE 800489797154 4
MAX NO LOAD VOLTAGE 4,2 V	ARMS PROJECTION 330 mm	PIECES/PALLET 3 pz/pallet



PCP 28 LCD 400V



RATED POWER X=50% 60 k VA



DUTY CYCLE 5,5 %

Included Accessories



STANDARD STRAIGHT ELECTRODE - 690035