

WaterWatch² Expansion Box

PN228067 WaterWatch² to Profibus DP Gateway

PRODUCT DATASHEET

COMPATIBLE MONITORS

7300w² Monitor (85 to 264VAC, Modbus Slave, 1 Relay Output)

7300w² Monitor (9 to 36VDC, Modbus Slave, 1 Relay Output)



The Profibus DP Gateway works with the 7300w² Monitor to provide measured variables, measurement status and product identity information from the monitor. Use of Profibus connectivity reduces installation costs and provides more information than is available over traditional 4-20 mA signals.

The expansion box is supplied with a 1 metre cable for connecting to the 7300w² Monitor and the enclosure is IP65 rated. The expansion box and monitor can be wall mounted but it is recommended that they are placed in a protective enclosure if they are to be mounted outdoors.

Physical

Dimensions Weight Protection Class Enclosure Material

Environmental Data

Operating Temperature Location

Electrical Information

Cable Type

Cable Length (to monitor)

Glands

Power Supply

Interface Type

Monitor to Expansion Expansion Box Output

170 x 280 x 60 mm (HxWxD) 0.55 kg (including 1m of cable)

IP65

ABS

-20 to 60°C

Indoor/Outdoor, wall or back of panel mounted

Connection from the monitor to the expansion box should be made using our Modtechw² cable

1 metre standard length is provided with the expansion box, additional lengths are available on request.

3 x M16 suitable for 4.5 to 10 mm cable Supplied by the 7300w² Monitor

Modbus RTU/RS485 Profibus DP via ADF Modbus to Profibus Converter

Order Codes

Part No Description

The company reserves the right to alter the specification without prior notice. E&OE

Call us on + 44(0) 1726 879800 www.partech.co.uk

