

# Homeowner Essentials 4-Piece Tool Kit



*Ideal for Everyday Home Maintenance and Inspection*



## **CBF200** **3-in-1 Circuit Breaker Finder**

Enables the safe identification of breaker locations within any electrical panel without removing power, check all your outlets for proper wiring, and test GFCI circuits for proper operation.



## **TMP10** **Digital Pocket Thermometer**

Quickly measures the temperature of air, liquids, and semi-solids. It's especially useful around the home for checking Hot/Cold water faucets, air vents or boiler, and its food-grade probe is even great for cooking.



## **IRT220** **Non-Contact 12:1 Infrared Thermometer**

Instantly measure an object's surface temperature without making contact. Use the IRT220 to check the electrical panel for any "hot" circuit breakers or check your heating/cooling vents for proper operation.



## **TPAL-X** **Autoloading Screwdriver**

Features an 18-tooth ratchet driver with forward, reverse, and lock. The on-hand bits save you time and let you quickly tighten loose hardware (cabinets, drawers, doors, windows, appliances, toys, and shelving). The perfect screwdriver for any new assembly projects.

# IRT220 Non-Contact 12:1 Laser IR Thermometer

**Instantly measure the temperature with Min/Max of objects without making contact**

## Features:

- Built-in laser identifies the measurement area
- Backlit LCD display with selectable °F or °C readout
- 0.95 fixed emissivity
- Min/Max to monitor lowest and highest measurement readings
- Automatic Data Hold
- Auto power off after 10 seconds
- Complete with 9V battery
- Optional model complete with Certificate of Traceability to N.I.S.T.
- 1-year warranty

## Applications:

- Measure the surface temperature of objects that are too hot to touch or hard to reach
- Measure moving objects



**NIST**  
TRACEABLE  
CALIBRATION  
AVAILABLE

## Specifications

Temperature Range	-4 to 932°F (-20 to 500°C)
Accuracy	±2%
Resolution	0.1°F/°C
Distance to Target Ratio	12:1
Response Time	500ms
Emissivity	0.95 fixed
Power	9V battery
Dimensions	5.4 x 2.9 x 1.5" (137 x 73 x 39mm)
Weight	5.2oz (148.5g)



## Ordering Information:

IRT220 Non-Contact 12:1 Laser IR Thermometer  
IRT220-NIST IRT220 Including Certificate of Traceability to N.I.S.T.

**CE**

# CBF200 3-in-1 Circuit Breaker Finder

## Circuit Breaker Finder, GFCI Receptacle Tester and Non-Contact Voltage (NCV) Detector

### Features:

- Safely identify and label breaker locations within any electrical panel without removing power
- Comparison mode helps to identify the correct breaker with the signal strengths are very close
- Detect faulty wiring in 3-wire receptacles
- Lights display 6 wiring faults:  
Open Ground, Open Neutral, Hot/Ground Reverse, Open Hot, Hot/Neutral Reverse, Hot on Neutral with Hot Open
- Test GFCI for proper operation
- Built-in Non-Contact Voltage Detector (80-300V, CAT III-300V)
- One person operation
- Includes Transmitter, Receiver and 9V Battery
- cETLus listed



### Applications:

- Useful, one person operation tool for residential and commercial electricians, home inspectors, kitchen and bath installers, apartment/condo property managers, DIY'ers and handymen

### Specifications

Transmitter	
Voltage	120VAC Single Phase Two Wires (Live, Neutral) with Ground
Frequency	47 ~ 63 Hz
GFCI Leakage Current	7mA @ 120VAC
Safety Standard	CAT II 300V
Receiver	
Battery	9V Alkaline x 1
Auto Shut Down	After 10 minutes without any operation
Non-Contact Voltage Detection	24-300VAC
Safety Standard	CAT III 300V
Transmitter Dimensions	4.7 x 2.5 x 1.3" (118.5 x 63 x 32mm)
Receiver Dimensions	5.1 x 2.4 x 1.5" (130 x 62 x 36.9mm)
Weight	9.8oz (260g)



### Ordering Information:

CBF200 3-in-1 Circuit Breaker Finder



# TPAL-X Professional Autoloader Multi Bit Screwdriver

*Perfect for the professional or do-it-yourselfer*

## **Features:**

- 18-tooth ratchet driver with forward, reverse and lock
- Custom-designed Bit Viewer lets you select the right bit instantly from the Quick-Change Barrel
- Comes with 2 Quick-Change Barrels and 12 bits, including: Slotted - 1/8", 5/32", 3/16"; Phillips - PH1, PH2, PH3; Hex - H3, H4, H5; Torx - T10, T15, T20
- Quick-Change Barrel stores in handle when not in use for quick access when needed
- Works with Triplet's TSBK-001 Security Bit-Kit set so you can make sure you always have your most-needed bits ready
- Lifetime warranty on mechanism; 1 year on bits.

## **Features:**

- Electronic/Appliance Repair
- Security Installation and Service
- MRO (Maintenance, Repair and Operation)



## **Ordering Information:**

TPAL-X Professional Autoloader Multi Bit Screwdriver

# TMP10 Pocket Thermometer

**Ideal for quick temperature checks**

## Features:

- 2.9" (73mm) stainless steel probe
- Data Hold freezes the reading on the display
- Min/Max with reset
- Complete with LR44 battery and protective probe cover
- 1-year warranty

## Applications:

- For measuring the temperature of air, liquids and semi-solids
- Food grade stainless steel probe



## Specifications

Temperature Range	-58 to 572°F (-50 to 300°C)
Accuracy	±1.8°F /1°C within 32 to 212°F (0 to 100°C); ±3.6°/2°C (other ranges)
Resolution	0.1°F/°C
Stem	2.9" (73mm) SUS304 Food Grade Stainless Steel
Power	LR44
Dimensions/Weight	5.7 x 0.8 x 0.5" (145 x 19.9 x 15mm) / 1oz (26g)



## Ordering Information:

TMP10      Pocket Thermometer