EMF85 8GHz Triple Axis EMF Meter

Designed for wide-band monitoring of high frequency radiation from 50MHz to 8GHz

Features:

- Non-directional measurement with built-in 3-axis (XYZ) probe
- Readout in 3 units of measure: μW/m², mW/m², W/m², μW/cm², mW/cm², mV/m , V/m
- Displays Actual, Average, Max and Max Average measurements
- Easy-to-read color LCD display with 4 brightness levels
- Programmable high alarm
- · Manually store/recall up to 10,000 points
- Historical data can be viewed on the display arranged in order of record and time
- USB interface for transfering recorded data to your PC in csv format
- Includes rechargeable 3.7V Li-ion battery, USB cable, and soft carrying case
- 1 year warranty

Applications:

- Measurement of electromagnetic radiation intensity of cellular phone base station antennas
- Wireless communication applications (CW, TDMA, GSM, DECT)
- · Safe use of RF high frequency electromagnetic waves
- · RF High Frequency Transmitter Power Measurement
- · Wireless Network (Wi-Fi) Detection, Installation
- · Wireless pinhole camera and eavesdropper detection
- Electromagnetic Radiation Intensity Measurement for Home Radio Telephone
- Detection of radiation leakage from microwave ovens
- Evaluation of electromagnetic wave safety in company or home environment



Specifications

Frequency Range	50MHz to 8GHz
Units of Measure	μW/m², mW/m², W/m²
	μW/cm², mW/cm²
	mV/m , V/m
Measurement Range	1μW/m² to 26.52W/m²
	0μW/cm² to 2.652mW/cm²
	20mV/m to 100V/m
Resolution	0.1µW/m², 0.001µW/cm², 0.1mV/m
Accuracy	±5%
Air Flow	Range (resolution)
	0 to 82998.3CFM (0.001CFM)
	0 to 282600CMM (0.001CMM)
Air Temperature	32 to 122°F/0 to 50°C (0.1°F/°C)
Memory	10,000 points (csv format)
PC Interface	USB
Power	Rechargeable 3.7V Li-ion battery
Dimensions	7.3 x 2.2 x 1.5" (185 x 55 x 38mm)
Weight	6oz (170g)

Ordering Information:

EMF85 8GHz Triple Axis EMF Meter



