



Model: 288X

288 Series Regulator

Designed for heavy duty gas welding, cutting and heating application. These regulators are ideal for industrial application.

- Body is machined from class "A" brass bar stock.
- Self re-seating external safety pressure relief valve on oxygen.
- Sintered bronze inlet filter.
- Stem type seat assembly for more reliable performance.
- 2" gauges for easy reading.
- Regulators verified by ECM, European standard EN 334:2005+A1:2009 and related to CE Directive 2014/68/EU (Pressure Equipment)

288X Two-Stage Oxygen Regulator

Specification	
Stock Code	FLW-GAR-02-288X
Gas Service	Oxygen
Model	288X
Max. Inlet Pressure (PSI)	3000
Max. Delivery Pressure (PSI)	175
Inlet Pressure Gauge	2" 4500PSI
Outlet Pressure Gauge	2" 250PSI
Inlet Connection	BSP 5/8"
Outlet Connection	3/8RH
Weight (KG)	1.36

288 Series Regulator

Designed for heavy duty gas welding, cutting and heating application. These regulators are ideal for industrial application.

- Body is machined from class "A" brass bar stock.
- Self re-seating external safety pressure relief valve on oxygen.
- Sintered bronze inlet filter.
- Stem type seat assembly for more reliable performance.
- 2" gauges for easy reading.
- Regulators verified by ECM, European standard EN 334:2005+A1:2009 and related to CE Directive 2014/68/EU (Pressure Equipment)

288Y Two-Stage Acetylene Regulator

Specification	
Stock Code	FLW-GAR-DA-288Y
Gas Service	Acetylene
Model	288Y
Max. Inlet Pressure (PSI)	400
Max. Delivery Pressure (PSI)	24.5
Inlet Pressure Gauge	2" 600PSI
Outlet Pressure Gauge	2" 35PSI
Inlet Connection	BSP 5/8"
Outlet Connection	3/8LH
Weight (KG)	1.32



Model: 288Y



EN 334:2005+A1:2009



CE Directive: 2014/68/EU