



Model: 88X

88 Series Regulator

Designed for heavy duty gas welding, cutting and heating application. These regulators are ideal for industrial application.

- Body is machined from class "A" brass bar stock.
- Self re-seating external safety pressure relief valve on oxygen.
- Sintered bronze inlet filter.
- Stem type seat assembly for more reliable performance.
- 2" gauges for easy reading.
- Regulators verified by ECM, European standard EN 334:2005+A1:2009 and related to CE Directive 2014/68/EU (Pressure Equipment)

88X Oxygen Regulator

Specification	
Stock Code	FLW-GAR-02-88X
Gas Service	Oxygen
Model	88X
Max. Inlet Pressure (PSI)	3000
Max. Delivery Pressure (PSI)	125
Inlet Pressure Gauge	2" 4000PSI
Outlet Pressure Gauge	2" 250PSI
Inlet Connection	BSP 5/8"
Outlet Connection	3/8RH
Weight (KG)	1.36

88 Series Regulator

Designed for heavy duty gas welding, cutting and heating application. These regulators are ideal for industrial application.

- Body is machined from class "A" brass bar stock.
- Self re-seating external safety pressure relief valve on oxygen.
- Sintered bronze inlet filter.
- Stem type seat assembly for more reliable performance.
- 2" gauges for easy reading.
- Regulators verified by ECM, European standard EN 334:2005+A1:2009 and related to CE Directive 2014/68/EU (Pressure Equipment)

88Y Acetylene Regulator

Specification	
Stock Code	FLW-GAR-DA-88Y
Gas Service	Acetylene
Model	88Y
Max. Inlet Pressure (PSI)	400
Max. Delivery Pressure (PSI)	20
Inlet Pressure Gauge	2" 600PSI
Outlet Pressure Gauge	2" 35PSI
Inlet Connection	BSP 5/8"
Outlet Connection	3/8LH
Weight (KG)	1.32



Model: 88Y



EN 334:2005+A1:2009



CE Directive: 2014/68/EU