

LONGLIFE complete



green-Effective Ultra-performance Floor Polish

■ Eco-efficient performance with eco-effective product design

User and environmental safety at the highest cleaning performance



- Developed to fulfil the Austrian Ecolabel
- Complete abandonment of toxic and harmful materials
- Outperforms other products at lower use concentration

Sustainable development and production



EMAS:

- Continuous improvement of environmental performance
- Annual sustainability report
- Energy and water
- management

Social Fairness DIN ISO 14001:



 Continuous improvement in reducing waste and CO2 emissions, and saving of energy, water and material consumption



ISO 50001:

 Continuous improvement of energy management: performance, efficiency, security, use and consumption



A.I.S.E.-Charter:

 Safe and sustainable manufacturing of cleaning products



DIN ISO 9001:

- Continuous improvement of management processes and customer satisfaction
- Established quality management system in product development and production

Intensive use of renewable resources - continuous increase of the reutilisation score



- Production under extensive use of renewable raw materials and energy using to 100% hydroelectric, solar and geothermic power
- Active water stewardship maintaining an own fresh and waste water treatment

Full transparency - complete ingredient declaration

<5% anionic surfactants (dialkylsulfosuccinate), non-ionic surfactants (fatty alcohol EO adduct), benzisothiazolinone, methylisothiazolinone, phenoxyethanol

Specific ingredients: water, acrylic-styrene copolymer, polyethylene wax, polypropylene wax, glycol ether, benzyl alcohol, softening agent (TBEP-free), levelling agents (non-fluorinated)

Traditional German quality - driving your durable business development



- More than 25 years pioneer in sustainable product development
- Smart hygiene solutions ensuring profitable growth
- Trusted brand

Professional user training and on-site support for Sustainable Hygiene Solutions



- Comprehensive knowledge transfer through qualified cleaning consultants
- Customized hygiene plans and cleaning recommendations optimizing your business and cleaning procedures
- Increased service value and strengthened company reputation





LONGLIFE complete



Application and Dosing



Dose in relation to application, Follow below instructions.



Floor preparation: strip the floor, remove all dirt and old dispersion layers.

Initial treatment: apply 2-3 thin and uniformlayers. Drying time between the applications at least



Large areas: work in sections and apply wet in wet. Usage: approx. 2 L / 100 m².



Coating refreshment: remove slight scratches using the spray-cleaner-method and a highspeed machine with red pad.

green-Effective® Ultra-performance Floor Polish

■ Complete economy ■ Complete safety ■ Complete flexibility

Product profile

- LONGLIFE complete provides the complete solution for highest standards in coating of hard and elastic floors combined with exceptional environmental properties.
- Meanwhile enhancing the work safety, LONGLIFE complete assures outstanding durability and resistibility even against alcohol and skin disinfectants as well as a long-life pleasant appearance and gloss.
- LONGLIFE complete is completely user safe due to its time-saving processability even on damp linoleum floors, its reduced slip hazard whilst stripping and its easy-to-use features. Its certification according DIN 18032-2 proves outstanding slip resistance.
- LONGLIFE complete is as flexible as an elastic coating, extremely adhesive and elastic and therefore, suitable for elastomer (rubber) flooring and areas with high point load.
- This product works ideally in a system with LINAX complete, which easily removes even multi-layer LONGLIFE complete polymer films.
- By the complete abandonment of hazardous ingredients such as zinc, TBEP and fluorinated levelling agents, LONGLIFE complete takes on the responsibility for future generations.

Area of application

- LONGLIFE complete is suitable for universal use on all coatable flooring especially elastic flooring made of PVC, linoleum, natural rubber and other special synthetic materials.
- Specially recommended for highly frequented areas, e.g. hospitals, schools, retail markets, airports, entrance areas etc. where high durability and long life cycle of coating is required.
- Not to be used on polished stone floors, stoneware tiles, as well as on unsealed wood.

Product safety, storage and environmental instructions

Safety: For professional use only. Keep away from children. Do not mix with other products. Test material compatibility before use. For further information, see Safety Data Sheet.

Storage: Store at room temperature in the original container. The storage and transport temperature of LONGLIFE complete must not exceed 30°C. Keep from freezing.

Environmental: Only give completely emptied packaging in the recommended waste container. Proper dosing saves costs and minimises environmental impact.



Your trusted partner on site

