

CENTER 337 Lightmeter

Our light meter CENTER 337 can be used in working environmental check, illumination design verification and other light monitoring applications. If the users turn on this unit with the cap on, it will zero the reading automatically. With the sensor on the top of tester, this meter can easily operate with single hand. The sensor is compensated with filter to make the response close to human eye. The light source angle is also compensated according to its cosine function.



FEATURES:

- 5 Digital Display
- Auto Ranging
- Automatic Power Off
- Fc / lx Function Selectable
- Hold Function
- Range Display
- Automatic Zero When Power On

SPECIFICATIONS

Light Range	0.000 ~ 4000 fc 0.00 ~ 40000 lx
Sample Rate	2 times/sec
Auto Power Off	30 minutes
Battery	9V battery
Dimensions	196x54x34 mm
Weight	Approx. 180g

STANDARD ACCESSORIES

Operation manual, Battery, Carry case.



CENTER 330 Anemometer

For air flow control application, CENTER 330 anemometer is a convenient tool to use. With the slim probe handle with extendable cable, it is easy to get the reading at location that the operator wants. With the built-in temperature measuring capability on the probe, the necessary data can be collected at the same time. It is also suitable for any application where air speed is considered and needs to be measured.



FEATURES:

- Dual Display
- Read While Measuring (Detached Vane)
- Hold/Max/ Min/Avg Function
- Auto Power Off

SPECIFICATIONS

Range	Airflow: 0.6 ~ 20m/sec, 120 ~ 4000 ft/min Temperature: -20°C ~ 60°C ; -4°F ~ 140°F
Resolution	Wind Speed-FTM: 0.1 m/s Temperature: 0.1°C / 0.1°F
Accuracy	Airflow: ±(2.5%rdg + 0.2m/s) Temperature: -20 ~ 60°C, ±0.8°C(±1.6°F)
Unit	m/sec, ft/min, km/hr, knots, °C/°F
Battery	9V battery
Dimensions	Meter: 186x64x30 mm ; Probe: 289(L) x 15(D) Sensor Head: 60.5mm Dia.
Weight	Approx. 362g

STANDARD ACCESSORIES

Operation manual, Battery, Probe Holder, Carry case.



LED Back Light

