



Services | Production metrology | Products | Precision gages | MarConnect - Data Processing | MarConnect - Wireless transmission | MarConnect - Integrated Wireless

WebCode 21557-117289

MARCONNECT I-STICK RECEIVER



Measurement without the nuisance of additional modules: Unlike conventional wireless solutions, which have a large external transmitter with separate battery, the transmitter in Integrated Wireless is fully integrated.

Highly mobile: Integrated Wireless gives you much more mobility. There is no cable to get in the way, either at the measuring station or when measuring on or at the machine or at large workpieces

Easy data transfer: With Integrated Wireless you can transfer your measured values to the PC simply using the iStick. As with a data cable, the measured values are accepted via the MarCom software directly into MS Excel© or via a keyboard code into any Windows application

Reliable transfer: With Integrated Wireless you can be sure that your data will arrive safely. Measuring instruments with Integrated Wireless display messages to confirm whether the transmitted data has been correctly transferred or whether you are within receiving range of the iStick receiver

Long battery life: The integrated wireless interface makes the measuring instrument exceptionally energy-efficient. And unlike conventional wireless systems, no additional battery is required

Affordable: With Integrated Wireless you can connect up to 8 measuring instruments per iStick receiver. Expensive interface boxes are no longer necessary. With even one connected measuring instrument you get a wireless connection for the price of a cable

Technical data

Order no.	Product type	Number of channels	Frequency band	Radio range	Number of connectable wireless receivers for i-stick	Number of connectable measuring instruments with integrated wireless	For measuring instrument	Data interface	Hardware interfaces	System requirements:
4102220	i-Stick	3	2,400 MHz	up to 6 m	4	32	MarCal 16 EWri / 30 EWri MarCator 1086 Ri / 1087 Ri / 1087 BRi Micromar 40 EWri	USB	USB	IBM AT compatible PC / CD- / DVD-drive / MS Excel from version 97 onwards / MS Windows 7 / USB-interface from version 1.1 / minimum 10 MB free hard disk space