CPA/CPB/CPC Series - Resolution 0.01g, 0.1g



CPA102-CPA2002



CPB122-CPB3002

| Model | CPA | CPA | CPA | CPA | CPB | CPB | CPB | CPB | CPD | CPD | CPD | CPD | |
|--------------|---------------------------|-----|-----|------|-----|-----|------|------|-----------------|------|------|-------|--|
| | 302 | 322 | 602 | 2002 | 602 | 622 | 1002 | 3002 | 3001 | 6001 | 6201 | 10001 | |
| Draft Shield | With Plastic Draft Shield | | | | | | | | No Draft Shield | | | | |

| Features | | | | | Benefits | | | | | | | | |
|--|--|--|----------|-------|--|------|-------|-------|-------|------------------------|-------|------|--|
| Economical and | Helps | Helps you save money with confidence | | | | | | | | | | | |
| Large stainless s | Allow | Allows for easy weighing of large objects | | | | | | | | | | | |
| Leveling feet with | Make | Makes it level even on uneven working surfaces | | | | | | | | | | | |
| Below balance w | Deter | Determines density of large pieces | | | | | | | | | | | |
| AC-DC available | | | | | Able to operate with rechargeable battery (not included) | | | | | | | | |
| LCD display with backlight | | | | | Allows for easy reading | | | | | | | | |
| Multiple weighing units Double TARE key | | | | | Allows for flexibility of weighing Easy for work to operate | | | | | | | | |
| Capacity | 300g | 320g | 600g | 2000g | 600g | 620g | 1000g | 3000g | 3000g | 6000g | 6200g | 10kg | |
| Resolution | 0.01 g 0.1 g | | | | | | | | | | | | |
| Repeatability | ± 0.02 g ± 0.2 g | | | | | | | | | | | | |
| Linearity Error | ± 0.02 g ± 0.2 g | | | | | | | | | | | | |
| Response Time | ≤ 2 sec | | | | | | | | | | | | |
| Calibration | Calibration with External Weight | | | | | | | | | | | | |
| Weighing Units | g, ct, lb, oz, ozt, dwt, kg, tmR, GSM, PKT etc(17 units) | | | | | | | | | | | | |
| Construction | Cast aluminum, static resistant ABS, stainless steel pan | | | | | | | | | | | | |
| Display | Large, easy to read LCD display with backlight | | | | | | | | | | | | |
| Pan Size | R | ound Par | n (115mr | n) | Square Pan,157 x 136mm | | | | | Square Pan,192 x 171mm | | | |
| Body dim. | 304x 204 x 300 mm 304x 204 x 90 mm | | | | | | | | | | n | | |
| Battery | Lithium battery | | | | | | | | | | | | |
| Power | 110v - 240v, 50HZ / 60HZ | | | | | | | | | | | | |
| Operational Temp. | 10 °C to 40 °C | | | | | | | | | | | | |
| Connectivity | Configurable RS 232 interface | | | | | | | | | | | | |