

# ULTRASONIC CUTTER ZO-80

"S-High mode" works to cut the object
1.5 times faster than the conventional model.\*1



Oscillation frequency 40kHz Max. power consumption Approx. 60W AC adapter 100-240 VAC 50/60 Hz OUTPUT: 12 VDC 5A \*2 Oscillator (main unit): 185\*169\*55 External dimensions (Unit: mm) (excluding protrusions) Hand-piece: φ28\*150 (including the blade) Power mode switch S-High/High/Normal Ambient condition Temperature: 5 to 35 ℃ Humidity: 20 to 70 %

(without condensation) \*3

Protection circuit

Temperature sensor inside of hand-piece. Detection circuit for insufficient tightened blade fixing screw and overload to the blade. Automatic stop after 10 minutes operation.

Weight Oscillator (main unit): Approx. 1.2kg

Hand-piece: Approx. 350g (including the hand-piece cable)


Accessories BDC-200P: 40 pcs./case

(including the blades with a hole)
Blade anchor ZH04: 1 pce.
Blade anchor screw HB03: 1 pce.
Hexagon wrench RR02: 1 pce.

\*1 Based on the comparison with the cutting speed of ZO-91 in High mode when 2mm thick acrylic is cut by the force of 2kgs.

<sup>\*2</sup> Accessory power cord complies with the Japanese law and safety standard based on the power voltage in Japan, 100VAC. In case the product is used in any foreign country or region, prepare and use the power cord which complies with the law and safety standard in the country or region by yourself.

<sup>\*3</sup> Ambient temperature in the ambient condition may not guarantee the performance of operation under the temperature.\*




● Synthetic resin ● Plastic

Epoxy putty

Silicone

● Paper / cardboard ● Chemical fiber / cloth

Polyester putty













## Blade anchor and set items

## **ZH04**

Standard blade anchor for ZO series



## **ZH04S**

Blade anchor set

- ·Blade anchor ZH04 x 1 ·Blade anchor screw HB03 x 1
- ·Hexagon wrench RR02 x 1



## **ZH14S**

Thin blade set

- •Thin blade ZH14 (5 pcs.) x 1
- •Blade anchor screw HB03 x 1
- ·Blade anchor ZH15 x 1



## **ZH16S**

Thin long blade set

- •Thin long blade ZH16 (5 pcs.) x 1



#### ZH-801

Foot switch for ZO-80

Optional items

Plug into the connector on the rear panel of ZO-80 to turn on and off ultrasonic vibration by the foot switch.



#### **ZH13**

Goggle

Wear goggles to protect your eyes from the broken blade.



#### SB01

Maintenance set



Abrasive paper x 3 Cleaning bar x 1

# **ZH15**

Blade anchor for Thin blade ZH14 and ZH16



## **ZH15S**

Blade anchor for thin blade set

- ·Blade anchor ZH15 x 1
- ·Blade anchor screw HB03 x 1
- ·Hexagon wrench RR02 x 1

## Replacement blades



## HA04

Long blade (25 mm)

**ZH10** 



**ZH18** 

Curving blade (4 mm)

**ZH03** 

Curving blade

Curving blade (2 mm) **ZH19** 

> Curving blade (3 mm)

**ZH20** 

Flat blade (1 mm)

**ZH05** 

Flat blade (2 mm)

ZH06

Flat plate (1 mm)

**ZH07** 

Flat plate (2 mm)

ZH08

Round tip blade (R15)

**ZH09** 

Round tip blade

**HA10** 

ZH11

Saw blade

Saw blade

**ZH37** 

Thin blade (5 pcs.)

ZH14

Thin long blade (5 pcs.)

**ZH16** 

Cemented carbide blade

HA07

Square blade

HA08

Square pyramid

**ZH12** 

Welding blade (2 mm)

**ZH38** 

Grinding stone #800 Color: Blue

**ZH24** 

Grinding stone #400 Color: Orange

**ZH29** 

Grinding stone #120 Color: Green

ZH26

Grinding stone #600 Color: Gray

**ZH30** 

Grinding stone #180 Color: Gold

**ZH27** 

Grinding stone #1000 Color: White

**ZH31** 

Grinding stone #300 Color: Brown

**ZH28** 

Grinding stone #1200 Color: Red

**ZH32** 

Filing plate #325 (4 mm)



Filing plate #325 (1 mm)

**BENEFOR ZH34** 

Filing plate #325 (2 mm)

5600 **ZH35** 

Filing plate #325 (3 mm)



Electrodeposited filing plate with square pyramid

**ZH39** 

We customize your original blades. Feel free to contact us for making your desirable blades.

General sales agent:



20 Oyamazuka, Oiwa-cho, Toyohashi, Aichi 441-3131

Tel:+81-532-65-5158/Fax:+81-532-65-5159

https/://www.echotech.co.jp/en/ worldinfo@us-dolphin.co.jp

Manufacturer:

HONDA ELECTRONICS CO.,LTD. 20 Oyamazuka, Oiwa-cho, Toyohashi, Aichi 441-3193 Registered company for ISO9001 and ISO14001

<Contact>