

Digital Indicator ID-S

12,7mm, 0,01mm, Flat Back

Item number: 543-781B



Description

This is a standard model of indicator that is reliable and easy to use. The ABSOLUTE Digimatic Indicator ID-S offers you the following benefits:

- The ABSOLUTE sensor means you don't have to carry out origin setting every time you power it on, saving you time and hassle.
- You can access all functions by using the large, user-friendly buttons on the front of the indicator.
- Large character height of 9 mm provides good readability.
 - Exceptional battery life.

Features

| | |
|--------------------------------|--|
| No. | 543-781 |
| Lug back plate: | |
| Range: | 12,7 mm |
| Digital step: | 0,01 mm |
| Max. Permissible Error E MPE: | 0,02 mm |
| H MPE (Hysteresis): | 0,02 mm |
| R MPE (Repeatability): | 0,01 mm |
| Type: | EN ISO Standard |
| Measuring force: | ≤ 1,5 N |
| Protection: | IP42 |
| Mass: | 140 g |
| Mass lug/plain: | 140/150 g |
| Display: | LCD, character height 9 mm |
| Max. response speed: | Unlimited |
| Alarm: | Low voltage, counting value composition error |
| Stem Ø: | 8 mm |
| Contact point: | Carbide ball, thread M 2.5 x 0.45 mm |
| Battery life: | approx. 18000 hours (0.001 mm type), approx. 20000 hours (0.01 mm type) |
| Power supply: | 1 battery SR-44 |
| Digimatic data output: | Yes |
| ON/OFF: | Yes |
| ORIGIN (ABS-Zero): | Yes |
| Counting direction switchable: | Yes |
| Digital/Analog: | Digital |
| Inch-Metric: | Metric |
| Delivered: | Including 1 battery |